

ISO 10555-6:2015-04 (E)

Intravascular catheters - Sterile and single-use catheters - Part 6: Subcutaneous implanted ports

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Requirements of the implantable subcutaneous implanted port and catheter	3
4.1	General	3
4.2	Biocompatibility	4
4.3	Distance markings	4
4.4	Nominal dimensions of the subcutaneous implanted port	4
4.5	Physical requirements	4
4.5.1	Radio-detectability	4
4.5.2	Surface finish	4
4.5.3	Freedom from leakage	4
4.5.4	Flushing volume	4
4.5.5	Characteristics of the septum	5
4.5.6	Characteristics of the connection or the catheter	5
4.6	Flow rate	5
4.6.1	Subcutaneous implanted ports not indicated for power injection	5
4.6.2	Subcutaneous implanted ports indicated for power injection	5
4.7	Burst pressure of the subcutaneous implanted port and catheter	6
4.7.1	Subcutaneous implanted ports not indicated for power injection	6
4.7.2	Subcutaneous implanted ports indicated for power injection	6
5	Magnetic Resonance Imaging (MRI) compatibility	6
6	Information to be supplied by the manufacturer	6
6.1	Marking on the device	6
6.2	Primary packaging	6
6.3	Labels for traceability	7
6.4	Instruction for use	7
Annex A (normative)	Test method for freedom from air leakage	8
Annex B (informative)	Determination of flushing volume	10
Annex C (informative)	Guidance on further characterization testing: Needle penetration and withdrawal	12
Annex D (normative)	Test method for freedom from leakage after multiple punctures	14
Annex E (normative)	Peak tensile force	15
Bibliography		16