

ISO 8537:2016-03 (E)

Sterile single-use syringes, with or without needle, for insulin

Contents		Page
Foreword	v	
Introduction	vi	
1 Scope	1	
2 Normative references	1	
3 Terms and definitions	2	
4 Types of syringes	5	
5 Requirements	5	
5.1 General requirements	5	
5.2 Material selection	6	
5.3 Colour coding	6	
5.4 Extraneous matter	7	
5.4.1 General	7	
5.4.2 Limits for acidity or alkalinity	7	
5.4.3 Limits for extractable metals	7	
5.5 Lubrication	7	
5.5.1 Lubrication of syringes	7	
5.5.2 Lubrication of needle tube	8	
5.6 Dimensions	8	
5.6.1 Barrel and plunger stopper	8	
5.6.2 Finger grips	8	
5.7 Plunger/plunger stopper	8	
5.7.1 General	8	
5.7.2 Fit of plunger stopper in barrel	8	
5.8 Nozzle	8	
5.8.1 Conical fitting	8	
5.8.2 Position of nozzle on end of barrel	8	
5.9 Needle tubing and needles	9	
5.9.1 Needles for syringe types 3 and 4	9	
5.9.2 Needle tubing for syringe types 5, 6, 7 and 8	9	
5.9.3 Bond between hub and needle tube	9	
5.10 Standard test environmental conditions	9	
5.11 Performance of assembled syringe	9	
5.11.1 Dead space	9	
5.11.2 Freedom from leakage at needle	10	
5.11.3 Freedom from leakage past plunger stopper	10	
6 Packaging	10	
6.1 Unit packaging and self-contained syringe units	10	
6.1.1 General	10	
6.1.2 Unit packaging providing sterile barrier syringes (types 1, 3, 5 and 7)	10	
6.1.3 Self-contained syringes with sterile interiors (types 2, 4, 6 and 8)	10	
6.2 Multiple-unit packaging (for syringe types 2, 4, 6 and 8)	11	
6.3 User packaging	11	
7 Information supplied by the manufacturer	11	
7.1 General	11	

7.2	Syringes	11
7.2.1	General	11
7.2.2	Additional marking for self-contained syringes (syringe types 2, 4, 6 and 8)	12
7.3	Unit packaging (for syringe types 1, 3, 5 and 7)	12
7.4	Multiple unit packs (syringe types 2, 4, 6 and 8)	12
7.5	User packaging	13
7.6	Storage container	14
7.7	Transport wrapping	14
Annex A (normative) Fluid for determination of acidity/alkalinity and extractable metals		15
Annex B (normative) Test method for air leakage past syringe piston during aspiration and for separation of rubber stopper and plunger		16
Annex C (normative) Test method for determination of forces required to operate piston		18
Annex D (normative) Test method for determination of dead space		20
Annex E (normative) Test method for liquid leakage at syringe piston and syringe nozzle/ hub or needle/barrel unions during compression		21
Annex F (normative) Test method for air leakage past nozzle/hub or needle/barrel unions during aspiration		23
Annex G (normative) Preparation of extract for test for pyrogenicity and toxicity		24
Annex H (normative) Syringe sizes and graduated scales		25
Bibliography		27