ISO 4802-2:2016-06 (E)

Glassware - Hydrolytic resistance of the interior surfaces of glass containers - Part 2: Determination by flame spectrometry a nd classification

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Principle 4

5 Reagents 4

6 Apparatus 6

7 Sample preparation 6
7.1 Sample size 6
7.2 Determination of the filling volume 7
7.2.1 Flat-bottomed containers 20 mm outer flange diameter (except ampoules, syringes and cartridges) 7
7.2.2 Flat-bottomed containers >20 mm outer flange diameter 7
7.2.3 Round-bottomed containers 7
7.2.4 Lipped containers 8
7.2.5 Ampoules 8
7.2.6 Syringes and cartridges 8

8 Procedure 8
8.1 General 8
8.2 Cleaning of samples 9
8.3 Filling and heating 9
8.4 Analysis of the extraction solutions 10
8.4.1 Containers of hydrolytic resistance container classes HCF 1, HCF 2 and HCF B or those known to be made from borosilicate glass 10
8.4.2 Containers of hydrolytic resistance container classes HCF 3 and HCF D, or those known to be made from soda-lime-silica glass 10
8.5 Testing to determine whether the containers have been surface-treated 11

9 Expression of results 11
9.1 Determination 11
9.2 Classification 12
9.3 Distinction between containers of hydrolytic resistance container class HCF 1 and hydrolytic resistance container class HCF 2 12
9.4 Designation 12

10 Test report 12

11 Reproducibility 13

Bibliography 14