

DIN ISO 4802-2:2017-02 (E)

Glassware - Hydrolytic resistance of the interior surfaces of glass containers - Part 2: Determination by flame spectrometry and classification (ISO 4802-2:2016)

Contents		Page
National foreword		3
Nationaler Annex NA (informative) Bibliography		4
Introduction		5
1 Scope		6
2 Normative references		6
3 Terms and definitions		6
4 Principle		9
5 Reagents		9
6 Apparatus		11
7 Sample preparation		11
7.1	Sample size	11
7.2	Determination of the filling volume	12
7.2.1	Flat-bottomed containers ≤20 mm outer flange diameter (except ampoules, syringes and cartridges)	12
7.2.2	Flat-bottomed containers >20 mm outer flange diameter	12
7.2.3	Round-bottomed containers	12
7.2.4	Lipped containers	13
7.2.5	Ampoules	13
7.2.6	Syringes and cartridges	13
8 Procedure		13
8.1	General	13
8.2	Cleaning of samples	14
8.3	Filling and heating	14
8.4	Analysis of the extraction solutions	15
8.4.1	Containers of hydrolytic resistance container classes HC _F 1, HC _F 2 and HC _F B or those known to be made from borosilicate glass	15
8.4.2	Containers of hydrolytic resistance container classes HC _F 3 and HC _F D, or those known to be made from soda-lime-silica glass	15
8.5	Testing to determine whether the containers have been surface-treated	16
9 Expression of results		16
9.1	Determination	16
9.2	Classification	17
9.3	Distinction between containers of hydrolytic resistance container class HC _F 1 and hydrolytic resistance container class HC _F 2	17
9.4	Designation	17
10 Test report		17
11 Reproducibility		18
Bibliography		19