

ISO 7886-1:2017-05 (E)

Sterile hypodermic syringes for single use - Part 1: Syringes for manual use

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Nomenclature	3
5	General requirements	5
6	Extraneous matter	5
6.1	General	5
6.2	Limits for acidity or alkalinity	5
6.3	Limits for extractable metals	5
7	Lubricant	6
8	Tolerance on graduated capacity	6
9	Graduated scale	7
9.1	Scale	7
9.2	Numbering of scales	8
9.3	Overall length of scale to nominal capacity line	8
9.4	Position of scale	9
10	Barrel	9
10.1	Dimensions	9
10.2	Barrel flanges	9
11	Plunger stopper/plunger assembly	9
11.1	Design	9
12	Nozzle	10
12.1	Conical fitting	10
12.2	Position of nozzle on end of barrel	10
12.3	Nozzle lumen	10
13	Performance	10
13.1	Dead space	10
13.2	Freedom from air and liquid leakage past plunger stopper	10
13.3	Force to operate the piston	10
13.4	Fit of plunger stopper/plunger in barrel	10
14	Packaging	11
14.1	Unit packaging and self-contained syringe units	11
14.1.1	Unit packaging	11
14.1.2	Self-contained syringe units	11
14.2	Multiple unit pack	11

14.3	User packaging	11
15	Information supplied by the manufacturer	12
15.1	General	12
15.2	Syringes	12
15.2.1	General	12
15.2.2	Additional marking for self-contained syringe units	12
15.3	Unit packaging	12
15.4	Multiple unit packs	13
15.4.1	General	13
15.4.2	Multiple unit packs with self-contained syringes	13
15.5	User packaging	13
15.6	Storage container	14
15.7	Transport wrapping	14
Annex A (normative) Method for preparation of extracts		15
Annex B (normative) Test method for air leakage past syringe plunger stopper during aspiration, and for separation of plunger stopper and plunger		16
Annex C (normative) Method for determination of dead space		18
Annex D (normative) Test method for liquid leakage at syringe plunger stopper under compression		19
Annex E (informative) Test method for the determination of forces required to operate the piston ..		21
Annex F (informative) Test method for the quantity of silicone		25
Bibliography		28