

# ISO 20698:2018 (E)

## Catheter systems for neuraxial application — Sterile and single-use catheters and accessories

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Intended performance
5	Design attributes
5.1	Nominal size of the catheter
5.1.1	General
5.1.2	Outside diameter
5.1.3	Catheter lengths
5.2	Catheter holes
5.3	Distal tip
5.4	Surface
5.5	Hubs
5.6	Markings
5.7	Filter
5.8	Stylet
5.9	Detectability
5.10	Fixation devices
6	Materials
6.1	General
6.2	Biocompatibility
6.3	Drug and material compatibility
7	Design evaluation
7.1	General
7.2	Pre-clinical evaluation
7.2.1	General
7.2.2	Radiopacity
7.2.3	Magnetic resonance compatibility
7.2.4	Corrosion resistance
7.2.5	Flow rate
7.2.6	Freedom from leakage (design)
7.2.7	Peak tensile force
7.2.8	Catheter kinking test
7.2.9	Surface
7.3	Clinical evaluation
8	Sterilization
8.1	General
8.2	Sterilization residuals
9	Packaging
10	Information to be supplied by the manufacturer

- 10.1 Marking on the device
- 10.2 Information on instructions for use and/or packaging

**Annex A (normative) Test method for resistance to corrosion**

- A.1 Principle
- A.2 Reagents
- A.3 Apparatus
- A.4 Procedure
- A.5 Test report

**Annex B (normative) Determination of flow rate through catheter**

- B.1 Principle
- B.2 Reagent
- B.3 Apparatus
- B.4 Procedure
- B.5 Expression of results
- B.6 Test report

**Annex C (normative) Test method for liquid leakage under pressure**

- C.1 Principle
- C.2 Reagents
- C.3 Apparatus
- C.4 Procedure
- C.5 Test report

**Annex D (normative) Method for determining peak tensile force**

- D.1 Principle
- D.2 Apparatus
- D.3 Procedure
- D.4 Test report

**Annex E (informative) Other units of measurement**

- E.1 General
- E.2 French or Charrière
- E.3 Needle gauge

Page count: 20