

# ISO 7886-4:2018 (E)

## Sterile hypodermic syringes for single use — Part 4: Syringes with re-use prevention feature

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Types of syringe
4.1	General
4.2	Types of re-use prevention feature
4.3	Types of intended use/application
5	Extraneous matter
5.1	General
5.2	Limits for acidity or alkalinity
5.3	Limits for extractable metals
6	Lubricant
7	Tolerance on graduated capacity
8	Graduated scale
8.1	Scale
8.2	Numbering of scale
8.3	Position of scale
8.4	Overall length of scale to nominal capacity line
9	Barrel
9.1	Dimensions
9.2	Barrel flanges
10	Plunger stopper/plunger assembly
10.1	Design
10.2	Fit of plunger stopper/plunger in the barrel
10.3	Fiducial line
11	Syringe nozzle/needle
11.1	Syringe with integrated needle
11.2	Syringe with Luer nozzle
12	Performance
12.1	Dead space
12.2	Freedom from air and liquid leakage
12.3	Re-use prevention feature
12.4	Performance after shipping
13	Packaging
13.1	Unit packaging and self-contained syringe units
13.2	Multiple unit pack
13.3	User packaging

**14 Information supplied by the manufacturer**

- 14.1 General**
- 14.2 Syringes**
  - 14.2.1 General**
  - 14.2.2 Unit packaging**
- 14.3 Multiple unit packs**
  - 14.3.1 General**
  - 14.3.2 Multiple unit packs with self-contained syringes**
- 14.4 User packaging**
  - 14.4.1 General**
  - 14.4.2 Storage container**
- 14.5 Transport wrapping**

**Annex A (normative) Method for preparation of extracts**

- A.1 Principle**
- A.2 Apparatus and reagents**
- A.3 Procedure**

**Annex B (normative) Test method for testing re-use prevention feature**

- B.1 Principle**
- B.2 Apparatus**
- B.3 Procedure**
  - B.3.1 Withdrawal test**
  - B.3.2 Back pressure**
- B.4 Test report**

**Page count: 10**