

ISO 7886-2:2020-04 (E)

Sterile hypodermic syringes for single use - Part 2: Syringes for use with power-driven syringe pumps

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Nomenclature | 1 |
| 5 | General requirements | 2 |
| 6 | Limits for acidity or alkalinity | 2 |
| 7 | Limits for extractable metals | 2 |
| 8 | Lubricant | 2 |
| 9 | Tolerance on graduated capacity | 2 |
| 10 | Graduated scale | 2 |
| 11 | Syringe design | 2 |
| 12 | Piston/plunger assembly | 4 |
| | 12.1 Design | 4 |
| | 12.2 Fit of plunger stopper/plunger in barrel | 4 |
| 13 | Nozzle | 4 |
| | 13.1 Conical fitting | 4 |
| | 13.2 Nozzle lumen | 4 |
| 14 | Performance | 4 |
| | 14.1 Dead space | 4 |
| | 14.2 Freedom from air and liquid leakage past the plunger stopper | 4 |
| | 14.3 Short-term flow rate error | 4 |
| | 14.4 Pump forces | 5 |
| | 14.5 Syringe compliance | 5 |
| 15 | Packaging | 6 |
| | 15.1 Unit packaging and self-contained syringe units | 6 |
| | 15.1.1 Unit packaging | 6 |
| | 15.1.2 Self-contained syringe units | 6 |
| | 15.2 Multiple unit pack | 6 |
| | 15.3 User packaging | 6 |
| 16 | Information supplied by the manufacturer | 6 |
| | 16.1 General | 6 |
| | 16.2 Syringes | 6 |
| | 16.2.1 General | 6 |
| | 16.2.2 Additional marking for self-contained syringe units | 7 |
| | 16.3 Unit packaging | 7 |
| | 16.4 Multiple unit packs | 7 |
| | 16.4.1 General | 7 |
| | 16.4.2 Multiple unit packs with self-contained syringes | 7 |
| | 16.5 User packaging | 7 |
| | 16.6 Storage container | 7 |
| | 16.7 Transport wrapping | 7 |

| | |
|--|-----------|
| Annex A (normative) Short-term flow rate accuracy | 8 |
| Annex B (informative) Pump force | 13 |
| Annex C (normative) Determination of syringe compliance | 15 |
| Bibliography | 17 |