

ISO 7439:2023-04 (E)

Copper-bearing contraceptive intrauterine devices - Requirements and tests

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Quality verification	2
5	Intended clinical performance	3
5.1	General	3
5.2	Clinical performance	3
5.2.1	General	3
5.2.2	Study duration	3
5.2.3	Study population	3
5.2.4	Sample size	4
5.2.5	Contraceptive performance	4
5.2.6	Expulsion rate	4
5.2.7	Discontinuation rate	4
5.2.8	Investigation report	4
5.2.9	Labelling	5
6	Design attributes	5
6.1	General	5
6.2	Shape	6
6.3	Dimensions	6
6.3.1	IUD	6
6.3.2	Copper components	6
6.3.3	Thread	6
6.3.4	Insertion instrument	6
6.4	Tensile force	6
6.5	Stability	7
6.5.1	Shelf-life stability	7
6.6	Viscoelastic property	7
6.7	Detection by X-ray	7
7	Materials	7
8	Design evaluation	7
8.1	General	7
8.2	Determination of dimensions	8
8.3	Determination of tensile force	8
8.3.1	Principle	8
8.3.2	Apparatus	8
8.3.3	Procedure	8
8.3.4	Test report	8
8.4	Test of elastic recovery (memory test)	9
8.4.1	Principle	9
8.4.2	Procedure	9

8.4.3	Test report	9
8.5	Determination of barium sulfate content and identification of barium and sulfate	9
8.5.1	Ash content test	9
8.5.2	Identity test	9
8.6	Pre-clinical evaluation	9
9	Manufacturing and inspection	10
10	Sterilization	10
11	Packaging	10
12	Information to be supplied by the manufacturer	10
12.1	General	10
12.2	Labelling of the primary container	11
12.3	Labelling of the secondary container	11
12.4	Instructions for the health care providers	11
12.5	Information intended for the client after insertion of the IUD	12
12.6	Written information intended for the client	13
	Annex A (normative) Sampling requirements for testing copper bearing IUDs	14
	Bibliography	16