ISO 4802-2:2023-12 (E)

Glassware - Hydrolytic resistance of the interior surfaces of glass containers - Part 2: Determination by flame spectrometry and classification

Contents

Page

Foreword ... **iv**

Introduction ... **v**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **1**

4 Principle ... **4**

5 Reagents ... **4**

6 Apparatus ... **6**

7 Sample preparation ... **7**
7.1 Sample size ... 7
7.2 Determination of the filling volume ... 7
7.2.1 Flat-bottomed containers ≤20 mm outer flange diameter (except ampoules, syringes and cartridges) ... 7
7.2.2 Flat-bottomed containers >20 mm outer flange diameter ... 7
7.2.3 Round-bottomed containers ... 8
7.2.4 Lipped containers ... 8
7.2.5 Ampoules ... 8
7.2.6 Syringes and cartridges ... 8

8 Procedure ... **9**
8.1 General ... 9
8.2 Cleaning of samples ... 9
8.3 Filling and heating ... 9
8.4 Analysis of the extraction solutions ... 10
8.4.1 Containers of hydrolytic resistance container classes HC_F 1, HC_F 2 and HC_F B or those known to be made from borosilicate glass ... 10
8.4.2 Containers of hydrolytic resistance container classes HC_F 3 and HC_F D, or those known to be made from soda-lime-silica glass ... 10
8.5 Test to determine whether the containers have been surface-treated ... 11

9 Expression of results ... **12**
9.1 Determination ... 12
9.2 Classification ... 12
9.3 Distinction between containers of hydrolytic resistance container class HC_F 1 and hydrolytic resistance container class HC_F 2 ... 13
9.4 Designation ... 13

10 Test report ... **13**

11 Reproducibility ... **13**

Bibliography ... **15**