

ISO 8009:2004-10 (E)

Mechanical contraceptives - Reusable natural and silicone rubber contraceptive diaphragms - Requirements and tests

| Contents | Page |
|--|-----------|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Sampling | 2 |
| 5 Classification | 2 |
| 6 Materials | 2 |
| 7 Design | 2 |
| 7.1 General | 2 |
| 7.2 Rim | 2 |
| 7.3 Reinforcing spring | 2 |
| 7.4 Spring ends | 2 |
| 7.5 Dome and rim | 3 |
| 8 Dimensions | 3 |
| 8.1 Diameter | 3 |
| 8.2 Dome thickness | 3 |
| 9 Tensile properties of the dome | 3 |
| 9.1 Tensile strength | 3 |
| 9.2 Elongation at break | 3 |
| 10 Type 1 and Type 2 diaphragms -- Mechanical properties of rim and spring | 4 |
| 10.1 Compression resistance | 4 |
| 10.2 Twisting during compression | 4 |
| 11 Freedom from visible defects | 4 |
| 12 Test report | 5 |
| 13 Packaging, labelling and storage | 5 |
| 13.1 Packaging | 5 |
| 13.2 Labelling | 5 |
| 13.3 Storage | 6 |
| Annex A (normative) Determination of size | 7 |
| Annex B (normative) Determination of dome thickness | 8 |
| Annex C (normative) Determination of tensile properties | 9 |
| Annex D (normative) Determination of deterioration after accelerated ageing by oven treatment | 11 |

| | |
|---|-----------|
| Annex E (normative) Determination of compression and fatigue resistances of coil-spring and flat-spring diaphragms | 13 |
| Annex F (normative) Determination of twisting during compression of coil-spring and flat spring diaphragms | 16 |
| Annex G (normative) Determination of visible defects | 19 |
| Annex H (normative) Test report | 23 |
| Annex I (normative) Instructions for care and use of reusable rubber contraceptive diaphragms | 24 |
| Bibliography | 26 |