

# DIN ISO 15759:2006-05 (E)

## Medical infusion equipment - Plastics caps with inserted elastomeric liner for containers manufactured by the blow-fill-seal (BFS) process (ISO 15759:2005)

---

| <b>Contents</b>            |  | <b>Page</b> |
|----------------------------|--|-------------|
| Foreword .....             |  | 2           |
| Introduction .....         |  | 2           |
| <b>1</b>                   | <b>Scope .....</b>   | <b>3</b>    |
| <b>2</b>                   | <b>Normative references .....</b>  | <b>3</b>    |
| <b>3</b>                   | <b>Dimensions and designation .....</b>  | <b>4</b>    |
| <b>3.1</b>                 | <b>Plastics cap for attachment by welding technique (Form A) .....</b>                               | <b>4</b>    |
| <b>3.2</b>                 | <b>Plastics cap for attachment by collar technique (Form B) .....</b>                                | <b>5</b>    |
| <b>3.3</b>                 | <b>Elastomeric liner .....</b>   | <b>6</b>    |
| <b>4</b>                   | <b>Materials for cap and liner .....</b>   | <b>6</b>    |
| <b>5</b>                   | <b>Plastics cap -- Physical requirements and testing .....</b>                                       | <b>7</b>    |
| <b>5.1</b>                 | <b>Leak-resistance test .....</b>  | <b>7</b>    |
| <b>5.2</b>                 | <b>Opening force .....</b>   | <b>7</b>    |
| <b>6</b>                   | <b>Liner -- Physical requirements and testing .....</b>  | <b>7</b>    |
| <b>6.1</b>                 | <b>General requirements .....</b>  | <b>7</b>    |
| <b>6.2</b>                 | <b>Hardness .....</b>  | <b>7</b>    |
| <b>6.3</b>                 | <b>Fragmentation (coring) .....</b>  | <b>7</b>    |
| <b>6.4</b>                 | <b>Penetration force .....</b>   | <b>7</b>    |
| <b>6.5</b>                 | <b>Dynamic spike-retention capability .....</b>  | <b>7</b>    |
| <b>6.6</b>                 | <b>Static spike-retention capability of the liner and leak resistance of the piercing area .....</b> | <b>7</b>    |
| <b>6.7</b>                 | <b>Resealability .....</b>   | <b>7</b>    |
| <b>7</b>                   | <b>Plastics cap -- Chemical requirements and testing .....</b>                                       | <b>7</b>    |
| <b>8</b>                   | <b>Liner -- Chemical requirements and testing .....</b>  | <b>8</b>    |
| <b>9</b>                   | <b>Biological requirements for plastics cap and liner .....</b>                                      | <b>8</b>    |
| <b>10</b>                  | <b>Packaging .....</b>   | <b>8</b>    |
| <b>11</b>                  | <b>Storage .....</b>   | <b>8</b>    |
| <b>12</b>                  | <b>Marking .....</b>   | <b>8</b>    |
| <b>Annex A (normative)</b> | <b>Leak-resistance test .....</b>  | <b>9</b>    |
| <b>Annex B (normative)</b> | <b>Opening force needed to expose the piercing area .....</b>  | <b>10</b>   |
| <b>Annex C (normative)</b> | <b>Fragmentation (coring) .....</b>  | <b>11</b>   |
| <b>Annex D (normative)</b> | <b>Penetration force .....</b>   | <b>12</b>   |
| <b>Annex E (normative)</b> | <b>Dynamic spike retention capability .....</b>  | <b>14</b>   |

|  |           |
|--|-----------|
| <b>Annex F (normative) Static spike-retention capability of the liner and leak resistance of the piercing area .....</b> | <b>15</b> |
| <b>Annex G (normative) Resealability .....</b>   | <b>16</b> |
| <b>Annex H (normative) Holding device for elastomeric liner .....</b>  | <b>17</b> |
| <b>Annex I (normative) Reference spike .....</b>   | <b>18</b> |
| <b>Bibliography .....</b>  | <b>19</b> |