DIN EN ISO 10846-2:2008-11 (E)

Acoustics and vibration - Laboratory measurement of vibro-acoustic transfer properties of resilient elements - Part 2: Direct method for determination of the dynamic stiffness of resilient supports for translatory motion (ISO 10846-2:2008)

Contents

Page

Foreword 3

Introduction 4

1 Scope 5

2 Normative references 6

3 Terms and definitions 7

4 Principle 10

5 Requirements for apparatus 10
5.1 Normal translations 10
5.2 Transverse translations 12
5.3 Suppression of unwanted vibrations 15

6 Criteria for adequacy of the test arrangement 16
6.1 Frequency range 16
6.2 Measurement of blocking force 16
6.3 Flanking transmission 17
6.4 Unwanted input vibrations 17
6.5 Accelerometers 18
6.6 Force transducers 18
6.7 Summation of signals 18
6.8 Analysers 19

7 Test procedures 19
7.1 Installation of the test elements 19
7.2 Selection of force measurement system and output-force distribution plates 19
7.3 Mounting and connection of accelerometers 19
7.4 Mounting and connections of the vibration exciter 20
7.5 Source signal 20
7.6 Measurements 20
7.7 Test for linearity 21

8 Evaluation of test results 22
8.1 Calculation of dynamic transfer stiffness 22
8.2 One-third-octave-band values of the frequency-averaged dynamic transfer stiffness 22
8.3 Presentation of one-third-octave-band results 23
8.4 Presentation of narrow-band data 24

9 Information to be recorded 25

10 Test report 26

Annex A (informative) Static load-deflection curve 27

Annex B (informative) Measurement uncertainty 28

Bibliography 32