

DIN EN ISO 10846-2:2008-11 (E)

Acoustics and vibration - Laboratory measurement of vibro-acoustic transfer properties of resilient elements - Part 2: Direct method for determination of the dynamic stiffness of resilient supports for translatory motion (ISO 10846-2:2008)

Contents		Page
Foreword		3
Introduction		4
1	Scope	5
2	Normative references	6
3	Terms and definitions	7
4	Principle	10
5	Requirements for apparatus	10
5.1	Normal translations	10
5.2	Transverse translations	12
5.3	Suppression of unwanted vibrations	15
6	Criteria for adequacy of the test arrangement	16
6.1	Frequency range	16
6.2	Measurement of blocking force	16
6.3	Flanking transmission	17
6.4	Unwanted input vibrations	17
6.5	Accelerometers	18
6.6	Force transducers	18
6.7	Summation of signals	18
6.8	Analysers	19
7	Test procedures	19
7.1	Installation of the test elements	19
7.2	Selection of force measurement system and output-force distribution plates	19
7.3	Mounting and connection of accelerometers	19
7.4	Mounting and connections of the vibration exciter	20
7.5	Source signal	20
7.6	Measurements	20
7.7	Test for linearity	21
8	Evaluation of test results	22
8.1	Calculation of dynamic transfer stiffness	22
8.2	One-third-octave-band values of the frequency-averaged dynamic transfer stiffness	22
8.3	Presentation of one-third-octave-band results	23
8.4	Presentation of narrow-band data	24
9	Information to be recorded	25
10	Test report	26
Annex A (informative) Static load-deflection curve		27
Annex B (informative) Measurement uncertainty		28
Bibliography		32