

DIN EN ISO 10846-2:2008-11 (E)

Acoustics and vibration - Laboratory measurement of vibro-acoustic transfer properties of resilient elements - Part 2: Direct method for determination of the dynamic stiffness of resilient supports for translatory motion (ISO 10846-2:2008)

| Contents | | Page |
|---|---|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Principle | 10 |
| 5 | Requirements for apparatus | 10 |
| 5.1 | Normal translations | 10 |
| 5.2 | Transverse translations | 12 |
| 5.3 | Suppression of unwanted vibrations | 15 |
| 6 | Criteria for adequacy of the test arrangement | 16 |
| 6.1 | Frequency range | 16 |
| 6.2 | Measurement of blocking force | 16 |
| 6.3 | Flanking transmission | 17 |
| 6.4 | Unwanted input vibrations | 17 |
| 6.5 | Accelerometers | 18 |
| 6.6 | Force transducers | 18 |
| 6.7 | Summation of signals | 18 |
| 6.8 | Analysers | 19 |
| 7 | Test procedures | 19 |
| 7.1 | Installation of the test elements | 19 |
| 7.2 | Selection of force measurement system and output-force distribution plates | 19 |
| 7.3 | Mounting and connection of accelerometers | 19 |
| 7.4 | Mounting and connections of the vibration exciter | 20 |
| 7.5 | Source signal | 20 |
| 7.6 | Measurements | 20 |
| 7.7 | Test for linearity | 21 |
| 8 | Evaluation of test results | 22 |
| 8.1 | Calculation of dynamic transfer stiffness | 22 |
| 8.2 | One-third-octave-band values of the frequency-averaged dynamic transfer stiffness | 22 |
| 8.3 | Presentation of one-third-octave-band results | 23 |
| 8.4 | Presentation of narrow-band data | 24 |
| 9 | Information to be recorded | 25 |
| 10 | Test report | 26 |
| Annex A (informative) Static load-deflection curve | | 27 |
| Annex B (informative) Measurement uncertainty | | 28 |
| Bibliography | | 32 |