ISO 10846-2:2008-08 (E)

Acous tics and vibration - Laboratory measurement of vibro-acoustic transfer properties of resilient elements - Part 2: Direct method for determination of the dynamic stiffness of resilient supports for translatory motion

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 2

3 Terms and definitions 3

4 Principle 6

5 Requirements for apparatus 6
5.1 Normal translations 6
5.2 Transverse translations 8
5.3 Suppression of unwanted vibrations 11

6 Criteria for adequacy of the test arrangement 12
6.1 Frequency range 12
6.2 Measurement of blocking force 12
6.3 Flanking transmission 13
6.4 Unwanted input vibrations 13
6.5 Accelerometers 14
6.6 Force transducers 14
6.7 Summation of signals 14
6.8 Analysers 15

7 Test procedures 15
7.1 Installation of the test elements 15
7.2 Selection of force measurement system and output-force distribution plates 15
7.3 Mounting and connection of accelerometers 15
7.4 Mounting and connections of the vibration exciter 16
7.5 Source signal 16
7.6 Measurements 16
7.7 Test for linearity 17

8 Evaluation of test results 18
8.1 Calculation of dynamic transfer stiffness 18
8.2 One-third-octave-band values of the frequency-averaged dynamic transfer stiffness 18
8.3 Presentation of one-third-octave-band results 19
8.4 Presentation of narrow-band data 20

9 Information to be recorded 21

10 Test report 22

Annex A (informative) Static load-deflection curve 23

Annex B (informative) Measurement uncertainty 24

Bibliography 28