

# ISO 10846-5:2008-08 (E)

## Acoustics and vibration - Laboratory measurement of vibro-acoustic transfer properties of resilient elements - Part 5: Driving point method for determination of the low-frequency transfer stiffness of resilient supports for translatory motion

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>2</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>3</b>
<b>4</b>	<b>Principle .....</b>	<b>5</b>
<b>5</b>	<b>Test arrangements .....</b>	<b>6</b>
5.1	Normal translations .....	6
5.2	Transverse translations .....	7
5.3	Suppression of unwanted vibrations .....	8
<b>6</b>	<b>Criteria for adequacy of the test arrangement .....</b>	<b>11</b>
6.1	General requirements .....	11
6.2	Determination of upper limiting frequency .....	12
6.3	Force transducers .....	12
6.4	Accelerometers .....	12
6.5	Summation of signals .....	13
6.6	Analysers .....	13
<b>7</b>	<b>Test procedures .....</b>	<b>13</b>
7.1	Selection of force measurement system and force distribution plates .....	13
7.2	Installation of the test element .....	13
7.3	Mounting and connection of accelerometers .....	14
7.4	Mounting and connections of the vibration exciter .....	14
7.5	Source signal .....	14
7.6	Measurements .....	14
7.7	Test for linearity .....	15
<b>8</b>	<b>Evaluation of test results .....</b>	<b>16</b>
8.1	Calculation of dynamic driving-point stiffness .....	16
8.2	One-third-octave-band values of the frequency-averaged dynamic driving-point stiffness .....	17
8.3	One-third-octave-band values of the frequency-averaged transfer stiffness .....	17
8.4	Presentation of one-third-octave-band results .....	17
8.5	Presentation of narrow-band data .....	18
<b>9</b>	<b>Information to be recorded .....</b>	<b>19</b>
<b>10</b>	<b>Test report .....</b>	<b>20</b>
<b>Annex A (informative) Static load-deflection curve .....</b>		<b>21</b>
<b>Annex B (informative) Measurement uncertainty .....</b>		<b>22</b>
<b>Bibliography .....</b>		<b>26</b>