ISO 10846-5:2008-08 (E)

Acoustics and vibration - Laboratory measurement of vibro-acoustic transfer properties of resilient elements - Part 5: Driving point method for determination of the low-frequency transfer stiffness of resilient supports for translatory motion

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 2

3 Terms and definitions 3

4 Principle 5

5 Test arrangements 6
5.1 Normal translations 6
5.2 Transverse translations 7
5.3 Suppression of unwanted vibrations 8

6 Criteria for adequacy of the test arrangement 11
6.1 General requirements 11
6.2 Determination of upper limiting frequency 12
6.3 Force transducers 12
6.4 Accelerometers 12
6.5 Summation of signals 13
6.6 Analysers 13

7 Test procedures 13
7.1 Selection of force measurement system and force distribution plates 13
7.2 Installation of the test element 13
7.3 Mounting and connection of accelerometers 14
7.4 Mounting and connections of the vibration exciter 14
7.5 Source signal 14
7.6 Measurements 14
7.7 Test for linearity 15

8 Evaluation of test results 16
8.1 Calculation of dynamic driving-point stiffness 16
8.2 One-third-octave-band values of the frequency-averaged dynamic driving-point stiffness 17
8.3 One-third-octave-band values of the frequency-averaged transfer stiffness 17
8.4 Presentation of one-third-octave-band results 17
8.5 Presentation of narrow-band data 18

9 Information to be recorded 19

10 Test report 20

Annex A (informative) Static load-deflection curve 21

Annex B (informative) Measurement uncertainty 22

Bibliography 26