

DIN 45673-5:2010-08 (E)

Mechanical vibration - Resilient elements used in railway tracks - Part 5: Laboratory test procedures for under-ballast mats

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Overview and general principles	5
4	Under-ballast mats for reducing vibrations, structure-borne noise and secondary air-borne noise	5
4.1	Static bedding modulus	5
4.2	Lower-frequency dynamic bedding modulus $C_{dyn 1}(f)$ for determining track dynamics	7
4.3	Lower-frequency dynamic stiffening ratio $dyn 1(10\text{ Hz})$	9
4.4	Higher-frequency dynamic bedding modulus $C_{dyn 2}(f)$ for determining the efficiency of mitigating structure-borne noise	9
4.5	Higher-frequency dynamic stiffening ratio $dyn 2(20\text{ Hz})$	10
4.6	Loss factor	11
5	Under-ballast mats to reduce ballast stress at high running speeds	11
5.1	Static bedding modulus	11
5.2	Dynamic bedding modulus for determining track dynamics	11
5.3	Lower-frequency dynamic stiffening ratio	11
5.4	Horizontal static bedding modulus $C_{stat,h}$	11
6	Fitness for purpose	12
6.1	General	12
6.2	Mechanical fatigue strength	13
6.3	Material identification testing	15
6.4	Material and component testing	15
7	Quality monitoring, quality assurance	18
Bibliography		19