

DIN 45669-1:2010-09 (E)

Measurement of vibration immission - Part 1: Vibration meters - Requirements and tests

| Contents | | Page |
|---|--|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 5 |
| 4 | Symbols | 10 |
| 5 | Requirements | 11 |
| 5.1 | General requirements | 11 |
| 5.2 | Specific requirements | 17 |
| 6 | Tests | 23 |
| 6.1 | General | 23 |
| 6.2 | Initial type test | 28 |
| 6.3 | Verification test | 37 |
| 6.4 | Intermediate test | 38 |
| 6.5 | Pre-measurement test | 39 |
| 7 | Mechanical calibration equipment | 41 |
| 7.1 | General | 41 |
| 7.2 | Back-to-back calibration | 41 |
| 7.3 | Calibration signals | 41 |
| 8 | Electrical calibration equipment | 42 |
| 8.1 | General | 42 |
| 8.2 | Calibration signals | 42 |
| 9 | Marking | 42 |
| 10 | Data sheet | 43 |
| 11 | Operating instructions | 43 |
| Annex A (informative) Examples of KBF signal generation | | 44 |
| Annex B (informative) Ripple | | 45 |
| Annex C (informative) Testing phase response characteristics by the tangent method | | 46 |
| Annex D (informative) Method for determining the significant frequency f _{mg} | | 48 |
| Annex E (normative) Method for assessing the effects of transient vibrations on building structures without determining the significant frequency | | 49 |
| Bibliography | | 52 |