

# ISO 16063-41:2011-08 (E)

## Methods for the calibration of vibration and shock transducers - Part 41: Calibration of laser vibrometers

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Classification of laser vibrometers and principles of test methods .....</b>	<b>2</b>
<b>4</b>	<b>Uncertainty of measurement .....</b>	<b>4</b>
<b>5</b>	<b>Requirements for apparatus and other conditions .....</b>	<b>5</b>
<b>6</b>	<b>Preferred amplitudes and frequencies .....</b>	<b>14</b>
<b>7</b>	<b>Common procedure for primary calibration (methods 1, 2 and 3) .....</b>	<b>15</b>
<b>8</b>	<b>Method using fringe counting (method 1) .....</b>	<b>15</b>
<b>9</b>	<b>Method using minimum-point detection (method 2) .....</b>	<b>16</b>
<b>10</b>	<b>Methods using sine approximation: method 3 (homodyne version) and method 3 (heterodyne version) .....</b>	<b>18</b>
<b>11</b>	<b>Method using comparison to a reference transducer (method 4) .....</b>	<b>20</b>
<b>12</b>	<b>Report of calibration results .....</b>	<b>21</b>
<b>Annex A (normative) Uncertainty components in the primary calibration by laser interferometry of vibration and shock transducers .....</b>		<b>31</b>
<b>Annex B (informative) Three versions of method 3 based on laser Doppler velocimetry .....</b>		<b>36</b>
<b>Annex C (informative) Example of calculation of measurement uncertainty in calibration of a laser vibrometer .....</b>		<b>40</b>
<b>Annex D (informative) Phase shift calibration of laser vibrometers .....</b>		<b>42</b>
<b>Bibliography .....</b>		<b>44</b>