

# ISO 18312-1:2012-01 (E)

## Mechanical vibration and shock - Measurement of vibration power flow from machines into connected support structures - Part 1: Direct method

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>iv</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>Fundamentals</b> .....	<b>3</b>
<b>5</b>	<b>Measurement</b> .....	<b>5</b>
<b>5.1</b>	<b>General</b> .....	<b>5</b>
<b>5.2</b>	<b>Arrangement of vibration transducers</b> .....	<b>5</b>
<b>5.3</b>	<b>Measurement of forces</b> .....	<b>5</b>
<b>5.4</b>	<b>Measurement equipment</b> .....	<b>7</b>
<b>5.5</b>	<b>Metrological specifications</b> .....	<b>8</b>
<b>5.6</b>	<b>Determination of upper frequency limit</b> .....	<b>9</b>
<b>5.7</b>	<b>Choice of number of joints to measure from</b> .....	<b>9</b>
<b>5.8</b>	<b>Determination of total vibration power by measuring from a limited number of joints</b> .....	<b>9</b>
<b>6</b>	<b>Measurement uncertainty</b> .....	<b>10</b>
<b>7</b>	<b>Data presentation and test report</b> .....	<b>10</b>
<b>Bibliography</b> .....		<b>12</b>