ISO 3095:2013-08 (E)

Acoustics - Railway applications - Measurement of noise emitted by railbound vehicles

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 2

4 Instrumentation and calibration 5
4.1 Instrumentation 5
4.2 Calibration 5

5 Stationary test 5
5.1 General 5
5.2 Environmental conditions 5
5.3 Track conditions 6
5.4 Vehicle conditions 6
5.5 Measurement positions 7
5.6 Measured quantities 8
5.7 Test procedure 8
5.8 Data processing 9

6 Constant speed test 10
6.1 Environmental conditions 10
6.2 Track conditions 11
6.3 Vehicle conditions 13
6.4 Measurement positions 16
6.5 Measured quantities 17
6.6 Test procedure 17
6.7 Data processing 20

7 Acceleration test from standstill 21
7.1 General 21
7.2 Environmental conditions 21
7.3 Track conditions 22
7.4 Vehicle conditions 22
7.5 Maximum level method 23
7.6 Averaged level method 25

8 Braking test 26
8.1 Environmental conditions 26
8.2 Track conditions 27
8.3 Vehicle conditions 27
8.4 Measurement positions 27
8.5 Measurement quantity 28
8.6 Test procedure 28
8.7 Data processing 28

9 Quality of the measurements 29

9.1 Deviations from the requirements 29
9.2 Measurement tolerances 29
9.3 Measurement spread 29
9.4 Measurement uncertainties 29

10 Test report 29

Annex A (normative) Method to characterize the impulsive character of the noise 31

Annex B (normative) Tests at constant speed -- Special cases 32

Annex C (normative) Method to assess acceptable small deviations from acoustic rail roughness requirements 37

Annex D (informative) Guidance for light rail vehicles measurement 39

Annex E (informative) Comparability of test situations in terms of acoustic rail roughness 43

Annex F (informative) Additional measurements 46

Annex G (informative)Quantificationofmeasurementuncertaintiesaccordingtol SO/ IEC Guide 98-3:2008[8] 47

Bibliography 52