

ISO/TR 17534-3:2015-01 (E)

Acoustics - Software for the calculation of sound outdoors - Part 3: Recommendations for quality assured implementation of ISO 9613-2 in software according to ISO 17534-1

Contents	Page
Foreword.....	v
Introduction.....	vi
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Identification of the official documentation.....	1
5 Additional recommendations.....	1
5.1 General.....	1
5.2 Screening.....	2
5.3 Limitation of the maximal possible attenuation by barriers.....	4
5.4 Calculation of the path-length difference, z	4
5.5 Diffraction with barrier on reflecting ground.....	4
5.6 No level increase caused by barriers due to lateral diffraction.....	4
5.7 No ground effect calculated with rays laterally diffracted.....	5
5.8 No lateral diffraction with elevated ground screening the direct ray.....	5
5.9 Multi-reflection.....	
the extension to reflections of higher orders.....	5
6 Test cases.....	6
6.1 General.....	6
6.2 Test cases with step by step results and final result interval.....	6
6.2.1 T01-T03.....	
Flat ground with homogeneous acoustic properties.....	6
6.2.2 T01.....	
Reflecting ground ($G = 0$).....	7
6.2.3 T02.....	
Mixed ground ($G = 0,5$).....	8
6.2.4 T03.....	
Porous ground ($G = 1$).....	9
6.2.5 T04.....	
Flat ground with spatially varying acoustic properties.....	9
6.2.6 T05.....	
Identical to T04, but calculation with the alternative method according to ISO 9613-2:1996, 7.3.2.....	11
6.2.7 T06.....	
Ground with spatially varying heights and acoustic properties.....	12
6.2.8 T07.....	
Identical to T06, but calculation with the alternative method according to ISO 9613-2:1996, 7.3.2.....	15
6.2.9 T08.....	
Flat ground with spatially varying acoustic properties and long barrier.....	16
6.2.10 T09.....	
Flat ground with spatially varying acoustic properties and short barrier.....	19
6.2.11 T10.....	
Ground with spatially varying heights and acoustic properties and short barrier.....	22

6.2.12	T11	24
	Flat ground with homogeneous acoustic properties and cubic building	
	receiver at low height.....	
6.2.13	T12	28
	Flat ground with homogeneous acoustic properties and cubic building	
	receiver at large height.....	
6.2.14	T13	31
	Flat ground with homogeneous acoustic properties and polygonal	
	building	
	receiver at low height.....	
6.2.15	T14	34
	Ground with spatially varying heights and acoustic properties and	
	polygonal building.....	
6.2.16	T15	37
	Flat ground with homogeneous acoustic properties and polygonal	
	building	
	receiver at large height.....	
6.2.17	T16	39
	Flat ground with homogeneous acoustic properties and three buildings.....	
6.2.18	T17	43
	Flat ground with homogeneous acoustic properties and three buildings ...	
	alternative position of source and receiver.....	
6.2.19	T18	46
	Flat ground with homogeneous acoustic properties and complex building	
	with backyard.....	
6.2.20	T19	50
	Ground with spatially varying heights and acoustic properties and	
	reflecting barrier.....	
7	Declaration of conformity (DOC).....	52
	Bibliography.....	56