

# DIN EN ISO 10848-1:2018-02 (E)

## Acoustics - Laboratory and field measurement of flanking transmission for airborne, impact and building service equipment sound between adjoining rooms - Part 1: Frame document (ISO 10848-1:2017)

---

<b>Contents</b>		<b>Page</b>
<b>European foreword</b>		<b>4</b>
<b>Foreword</b>		<b>5</b>
<b>1</b>	<b>Scope</b>	<b>6</b>
<b>2</b>	<b>Normative references</b>	<b>6</b>
<b>3</b>	<b>Terms and definitions</b>	<b>7</b>
<b>4</b>	<b>Quantities to characterize flanking transmission</b>	<b>12</b>
4.1	General	12
4.2	Normalized flanking level difference, $D_{n,f}$ , normalized flanking impact sound pressure level, $L_{n,f}$ and normalized flanking equipment sound pressure level, $L_{ne0,f}$	13
4.2.1	General	13
4.2.2	$D_{v,ij,n}$ estimated from measurements of $D_{n,f}$	13
4.3	Vibration reduction index, $K_{ij}$	13
4.3.1	General	13
4.3.2	$K_{ij}$ for combinations of Type A and B elements	14
4.3.3	Strong coupling between Type A elements	14
4.4	Normalized direction-average vibration level difference, $\overline{D_{v,ij,n}}$	14
4.4.1	General	14
4.5	Selection of the measurement method	15
<b>5</b>	<b>Instrumentation</b>	<b>15</b>
5.1	General	15
5.2	Verification	16
<b>6</b>	<b>General requirements for test facility and test elements</b>	<b>16</b>
6.1	Laboratory	16
6.2	Field	19
<b>7</b>	<b>Measurement methods</b>	<b>19</b>
7.1	Measurement of $D_{n,f}$ , $L_{n,f}$ and $L_{ne0,f}$	19
7.1.1	Generation of sound field in the source room	19
7.1.2	Measurement of the average sound pressure level	21
7.1.3	Measurement of reverberation time and evaluation of the equivalent sound absorption area	23
7.2	Measurement of $K_{ij}$ and $\overline{D_{v,ij,n}}$	23
7.2.1	General aspects for $K_{ij}$	23
7.2.2	General aspects for $\overline{D_{v,ij,n}}$	23
7.2.3	Vibration measurement	24
7.2.4	Generation of vibration on the source element	25
7.2.5	Procedure for Type A and B elements	25
7.2.6	Steady-state excitation	26
7.2.7	Transient excitation	27
7.3	Measurement of the structural reverberation time for Type A elements	27
7.3.1	General	27
7.3.2	Excitation of the test element	27
7.3.3	Measurement and excitation positions	28
7.3.4	Evaluation of the decay curves	28
7.3.5	Lower limits for reliable results caused by filter and detector	29
7.4	Frequency range of measurement	29

<b>8</b>	<b>Influences from other parts of the test facility or the building construction in the field situation</b> .....	<b>24</b>
8.1	Laboratory installations of test junctions.....	24
8.2	Criterion to assess flanking transmission for junctions comprised of Type A elements.....	25
8.2.1	General.....	25
8.2.2	Practical considerations.....	25
8.3	Verification procedure for a Type B flanking element that is structurally independent of a separating element.....	25
<b>9</b>	<b>Shielding</b> .....	<b>26</b>
<b>10</b>	<b>Expression of results</b> .....	<b>26</b>
<b>Annex A (normative)</b>	<b>Assessing the decrease in vibration level with distance</b> .....	<b>28</b>
<b>Annex B (normative)</b>	<b>Calibrated structure-borne sound source</b> .....	<b>30</b>
<b>Bibliography</b>	.....	<b>34</b>