

# ISO 20155:2017-08 (E)

## Ships and marine technology - Test method of flow induced in-pipe noise source characteristics for a ship-used pump

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Two-port source model and test method of source characteristic of pump .....	2
4.1	Two-port source model of a pump .....	2
4.2	Test methods for source characteristic parameters of the pump .....	3
5	Test rig .....	4
5.1	Test loop .....	4
5.2	Installation of test pump .....	5
5.3	Ground foundation and supporting structure .....	6
5.4	Test-bed pipeline .....	6
5.5	Test section .....	6
5.6	Throttling valve .....	6
5.7	Secondary acoustic exciter .....	7
5.8	Water tank .....	7
6	Instrumentation .....	7
6.1	General .....	7
6.2	Static measurements .....	7
6.3	Dynamic measurements .....	7
7	Test preparation .....	8
8	Test procedure .....	8
9	Data processing .....	9
9.1	General .....	9
9.2	Passive characteristic of noise source .....	9
9.3	Active characteristic .....	9
10	Evaluation criteria for the test result .....	9
11	Test report .....	10
11.1	Overview .....	10
11.2	General information .....	10
11.3	Test record .....	11
11.4	Test result .....	11
Annex A (informative)	Theoretical models of a two-port source and transformation mutually between matrix Z, S, T .....	13
Annex B (informative)	Evaluation of quantities at inlet and outlet ports .....	15

<b>Annex C (informative) Judgment of effectiveness for the test .....</b>	<b>17</b>
<b>Annex D (informative) Formulae for determining passive characteristics of noise source .....</b>	<b>19</b>
<b>Annex E (informative) Formulae for determining active characteristics of source .....</b>	<b>20</b>
<b>Annex F (informative) Verification of test method taking a T-shaped sound excitor as a two- port acoustic source .....</b>	<b>21</b>
<b>Bibliography .....</b>	<b>24</b>