ISO 20155:2017-08 (E)

Ships and marine technology - Test method of flow induced in-pipe noise source characteristics for a ship-used pump

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Two-port source model and test method of source characteristic of pump 2
4.1 Two-port source model of a pump 2
4.2 Test methods for source characteristic parameters of the pump 3

5 Test rig 4
5.1 Test loop 4
5.2 Installation of test pump 5
5.3 Ground foundation and supporting structure 6
5.4 Test-bed pipeline 6
5.5 Test section 6
5.6 Throttling valve 6
5.7 Secondary acoustic exciter 7
5.8 Water tank 7

6 Instrumentation 7
6.1 General 7
6.2 Static measurements 7
6.3 Dynamic measurements 7

7 Test preparation 8

8 Test procedure 8

9 Data processing 9
9.1 General 9
9.2 Passive characteristic of noise source 9
9.3 Active characteristic 9

10 Evaluation criteria for the test result 9

11 Test report 10
11.1 Overview 10
11.2 General information 10
11.3 Test record 11
11.4 Test result 11

Annex A (informative) Theoretical models of a two-port source and transformation mutually between matrix Z, S, T 13

Annex B (informative) Evaluation of quantities at inlet and outlet ports 15

Annex C (informative) Judgment of effectiveness for the test 17

Annex D (informative) Formulae for determining passive characteristics of noise source 19

Annex E (informative) Formulae for determining active characteristics of source 20

Annex F (informative) Verification of test method taking a T-shaped sound excitor as a two- port acoustic source 21

Bibliography 24