

ISO 20155:2017-08 (E)

Ships and marine technology - Test method of flow induced in-pipe noise source characteristics for a ship-used pump

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Two-port source model and test method of source characteristic of pump	2
4.1	Two-port source model of a pump	2
4.2	Test methods for source characteristic parameters of the pump	3
5	Test rig	4
5.1	Test loop	4
5.2	Installation of test pump	5
5.3	Ground foundation and supporting structure	6
5.4	Test-bed pipeline	6
5.5	Test section	6
5.6	Throttling valve	6
5.7	Secondary acoustic exciter	7
5.8	Water tank	7
6	Instrumentation	7
6.1	General	7
6.2	Static measurements	7
6.3	Dynamic measurements	7
7	Test preparation	8
8	Test procedure	8
9	Data processing	9
9.1	General	9
9.2	Passive characteristic of noise source	9
9.3	Active characteristic	9
10	Evaluation criteria for the test result	9
11	Test report	10
11.1	Overview	10
11.2	General information	10
11.3	Test record	11
11.4	Test result	11
Annex A (informative)	Theoretical models of a two-port source and transformation mutually between matrix Z, S, T	13
Annex B (informative)	Evaluation of quantities at inlet and outlet ports	15

Annex C (informative) Judgment of effectiveness for the test	17
Annex D (informative) Formulae for determining passive characteristics of noise source	19
Annex E (informative) Formulae for determining active characteristics of source	20
Annex F (informative) Verification of test method taking a T-shaped sound excitor as a two- port acoustic source	21
Bibliography	24