

ISO 20155:2017-08 (E)

Ships and marine technology - Test method of flow induced in-pipe noise source characteristics for a ship-used pump

| Contents | | Page |
|-----------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Two-port source model and test method of source characteristic of pump | 2 |
| 4.1 | Two-port source model of a pump | 2 |
| 4.2 | Test methods for source characteristic parameters of the pump | 3 |
| 5 | Test rig | 4 |
| 5.1 | Test loop | 4 |
| 5.2 | Installation of test pump | 5 |
| 5.3 | Ground foundation and supporting structure | 6 |
| 5.4 | Test-bed pipeline | 6 |
| 5.5 | Test section | 6 |
| 5.6 | Throttling valve | 6 |
| 5.7 | Secondary acoustic exciter | 7 |
| 5.8 | Water tank | 7 |
| 6 | Instrumentation | 7 |
| 6.1 | General | 7 |
| 6.2 | Static measurements | 7 |
| 6.3 | Dynamic measurements | 7 |
| 7 | Test preparation | 8 |
| 8 | Test procedure | 8 |
| 9 | Data processing | 9 |
| 9.1 | General | 9 |
| 9.2 | Passive characteristic of noise source | 9 |
| 9.3 | Active characteristic | 9 |
| 10 | Evaluation criteria for the test result | 9 |
| 11 | Test report | 10 |
| 11.1 | Overview | 10 |
| 11.2 | General information | 10 |
| 11.3 | Test record | 11 |
| 11.4 | Test result | 11 |
| Annex A (informative) | Theoretical models of a two-port source and transformation mutually between matrix Z, S, T | 13 |
| Annex B (informative) | Evaluation of quantities at inlet and outlet ports | 15 |

| | |
|---|-----------|
| Annex C (informative) Judgment of effectiveness for the test | 17 |
| Annex D (informative) Formulae for determining passive characteristics of noise source | 19 |
| Annex E (informative) Formulae for determining active characteristics of source | 20 |
| Annex F (informative) Verification of test method taking a T-shaped sound excitor as a two- port acoustic source | 21 |
| Bibliography | 24 |