

ISO 10848-2:2017-09 (E)

Acoustics - Laboratory and field measurement of flanking transmission for airborne, impact and building service equipment sound between adjoining rooms - Part 2: Application to Type B elements when the junction has a small influence

| Contents | | Page |
|-----------------|--|-------------|
| | Foreword | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Instrumentation | 3 |
| 5 | Test arrangement | 3 |
| 5.1 | Requirements for the laboratory..... | 3 |
| 5.1.1 | General..... | 3 |
| 5.1.2 | Construction of the test facility..... | 3 |
| 5.1.3 | Dimensions of the test facility..... | 4 |
| 5.1.4 | Dividing wall..... | 4 |
| 5.1.5 | Plenum height..... | 4 |
| 5.1.6 | Plenum lining..... | 4 |
| 5.2 | Installation of the test element..... | 5 |
| 5.2.1 | Installation of access floors..... | 5 |
| 5.2.2 | Installation of suspended ceilings..... | 5 |
| 5.2.3 | Installation of a façade..... | 7 |
| 5.2.4 | Installation of a partition wall..... | 7 |
| 5.3 | Verification procedure for a light flanking element that is structurally independent of a separating element..... | 8 |
| 5.4 | Shielding technique used in the case of airborne excitation..... | 9 |
| 6 | Test procedures | 9 |
| 7 | Precision | 9 |
| 8 | Expression of results | 9 |
| 9 | Test report | 10 |
| | Annex A (informative) Measurement of $D_{n,f,l}$, $L_{n,f,l}$ and $L_{ne0,f,l}$ with sound intensity | 11 |
| | Bibliography | 12 |