

ISO 16283-2:2018 (E)

Acoustics — Field measurement of sound insulation in buildings and of building elements — Part 2: Impact sound insulation

Contents

| | |
|-------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Instrumentation |
| 4.1 | General |
| 4.2 | Calibration |
| 4.3 | Verification |
| 5 | Frequency range |
| 5.1 | Tapping machine as the impact source |
| 5.2 | Rubber ball as the impact source |
| 6 | General |
| 7 | Default procedure for sound pressure level measurement |
| 7.1 | General |
| 7.2 | Generation of sound field |
| 7.2.1 | General |
| 7.2.2 | Impact source positions for the tapping machine as impact source |
| 7.2.3 | Impact source positions for the rubber ball as impact source |
| 7.3 | Fixed microphone positions for the tapping machine or rubber ball as impact source |
| 7.3.1 | General |
| 7.3.2 | Number of measurements |
| 7.3.3 | Tapping machine operated at more than one position |
| 7.3.4 | Rubber ball operated at more than one position |
| 7.4 | Mechanized continuously moving microphone for the tapping machine as impact source |
| 7.4.1 | General |
| 7.4.2 | Number of measurements |
| 7.4.3 | Tapping machine operated at more than one position |
| 7.5 | Manually scanned microphone for the tapping machine as impact source |
| 7.5.1 | General |
| 7.5.2 | Number of measurements |
| 7.5.3 | Tapping machine operated at more than one position |
| 7.5.4 | Circle |
| 7.5.5 | Helix |
| 7.5.6 | Cylindrical-type |
| 7.5.7 | Three semicircles |
| 7.6 | Minimum distances for microphone positions |
| 7.7 | Averaging times for the tapping machine as impact source |
| 7.7.1 | Fixed microphone positions |
| 7.7.2 | Mechanized continuously moving microphone |
| 7.7.3 | Manually scanned microphone |
| 7.8 | Calculation of energy-average sound pressure levels |
| 7.8.1 | Fixed microphone positions for the tapping machine as impact source |

- 7.8.2 Mechanized continuously moving microphone and manually scanned microphone for the tapping machine as impact source
- 7.8.3 Fixed microphone positions for the rubber ball as impact source
- 8 Low-frequency procedure for sound pressure level measurement for the tapping machine as impact source
 - 8.1 General
 - 8.2 Generation of sound field
 - 8.2.1 General
 - 8.2.2 Impact source positions
 - 8.3 Microphone positions
 - 8.4 Averaging time
 - 8.5 Calculation of low-frequency energy-average impact sound pressure levels
- 9 Background noise (default and low-frequency procedure)
 - 9.1 General
 - 9.2 Correction to the signal level for background noise
- 10 Reverberation time in the receiving room (default and low-frequency procedure)
 - 10.1 General
 - 10.2 Generation of sound field
 - 10.3 Default procedure
 - 10.4 Low-frequency procedure
 - 10.5 Interrupted noise method
 - 10.6 Integrated impulse response method
- 11 Conversion to octave bands
- 12 Expression of results
- 13 Uncertainty
- 14 Test report
- Annex A (normative) Impact sources
 - A.1 Standard tapping machine
 - A.1.1 Requirements
 - A.1.2 Regular checks of performance
 - A.2 Rubber ball
 - A.2.1 Requirements
 - A.2.2 Example of construction of the rubber ball
 - A.2.3 Regular checks of performance
- Annex B (normative) Requirements for loudspeakers used for reverberation time measurements
 - B.1 General
 - B.2 Qualification procedure for directivity
- Annex C (informative) Forms for the expression of results
- Annex D (informative) Additional guidance
 - D.1 General
 - D.2 Principles
 - D.2.1 Floor coverings
 - D.2.2 Calculation of room volumes
 - D.2.3 Calculation of common partition area
 - D.2.4 Number of microphone and impact source positions
 - D.3 Horizontal measurements
 - D.4 Vertical measurements
 - D.4.1 General
 - D.4.2 Partly divided rooms
 - D.4.3 Non-staggered rooms
 - D.4.3.1 General
 - D.4.3.2 Rooms with floor area of the source room equal to or less than the floor area of the receiving room

- D.4.3.3 Rooms with floor area of the source room larger than the floor area of the receiving room
 - D.4.4 Staggered rooms
 - D.5 Corridors and staircases
 - D.5.1 Measurements of impact sound insulation from a corridor
 - D.5.2 Measurements of impact sound insulation from staircases in apartment houses and internal stairs in apartments and terrace houses
 - D.6 Airborne sound contribution from the tapping machine
- Annex E (informative) Horizontal measurements — Examples of suitable impact source and microphone positions
- E.1 General
 - E.2 Symbols
- Annex F (informative) Vertical measurements — Examples of suitable impact source and microphone positions
- F.1 General
 - F.2 Symbols

Page count: 44