

ISO 20816-5:2018 (E)

Mechanical vibration — Measurement and evaluation of machine vibration — Part 5: Machine sets in hydraulic power generating and pump-storage plants

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Machine arrangements
5	Measurement procedures and conditions
5.1	General
5.1.1	Bearing housing vibration measurements
5.1.2	Shaft vibration measurements
5.2	Measurement types
5.2.1	Absolute bearing housing vibration
5.2.2	Radial shaft vibration
5.2.2.1	General
5.2.2.2	Relative shaft vibration measurements
5.2.2.3	Absolute shaft vibration measurements
5.2.3	Bearing and shaft vibration in the axial direction
5.2.4	Detrimental influences
5.3	Measurement locations and directions
5.3.1	General
5.3.2	Measurement of relative shaft vibration
5.3.3	Measurement of the absolute bearing housing vibration
5.4	Measurement equipment
5.4.1	General
5.4.2	Absolute bearing housing vibration measurements
5.4.3	Shaft vibration measurement
5.4.4	Measurement of S_{max} or S_{p-p}
5.5	Operational conditions
6	Evaluation of vibration measurements
6.1	General
6.1.1	Basis of the vibration values
6.1.2	Effect of turbine operating conditions on bearing housing vibration measurements
6.1.3	Effect of turbine operating conditions on shaft vibration
6.1.4	Pump operating conditions
6.1.5	Special operating conditions
6.2	Criterion I: Vibration magnitude
6.3	Criterion II: Change in vibration magnitude and phase
6.3.1	Assessment criteria
6.3.2	Monitoring prerequisites
6.3.3	Specific recommendation related to the generator
6.4	Operational limits
6.4.1	Alarms and trips
6.4.2	Setting of alarms
6.4.3	Setting of trips
6.4.4	Special operating conditions
6.5	Comparison of results for shaft vibration and bearing housing vibration

- 6.6 Evaluation based on vibration vector information**
- Annex A (normative) Evaluation zone boundaries**
 - A.1 Vibration action limits**
 - A.2 Application of the specified limit values and actions**
 - A.3 Actions to be taken when the action limits are exceeded**
 - A.3.1 Action limit 1**
 - A.3.2 Action limit 2**
 - A.4 Examples of measured vibration values**
- Annex B (informative) Vibration monitoring — Prerequisite for trend analysis**
 - B.1 General information and recommendation**
 - B.2 Basic physical principle for bearing vibration**
- Annex C (informative) Special features of bearing housing vibration and shaft vibration of hydraulic machine sets**
 - C.1 General**
 - C.2 Frequencies of vibration from mechanical and electrical source**
 - C.3 Mechanical causes**
 - C.4 Electrical causes**
 - C.5 Hydraulic causes**
 - C.5.1 Significant frequencies in the water flow through the water passages**
 - C.5.2 Draft tube flow instabilities**
 - C.5.3 Cavitation**
 - C.5.4 Self-excited vibration**
 - C.5.5 Hydraulically excited vibration**
 - C.6 Additional excitations**
- Annex D (informative) Database, analysis procedure and statistical evaluation**
 - D.1 Collection of measured shaft and bearing housing vibration values**
 - D.2 Statistical evaluation**
- Annex E (informative) Recommended practice for vibration data processing**
 - E.1 General**
 - E.2 Possible data filtering in the time domain**
 - E.3 Possible data filtering in the frequency domain**
 - E.4 Details of the peak-to-peak evaluation**
 - E.4.1 Evaluation procedure**
 - E.4.2 Major findings**
 - E.4.2.1 General**
 - E.4.2.2 Standard deviation based evaluation**
 - E.4.2.3 (Mean) peak-to-peak value of subsets**
 - E.4.2.4 Percentile**