

# DIN EN ISO 16283-2:2018-11 (E)

## Acoustics - Field measurement of sound insulation in buildings and of building elements - Part 2: Impact sound insulation (ISO 16283-2:2018)

---

| <b>Contents</b>   |  | <b>Page</b> |
|---|--|-------------|
| <b>European foreword</b> .....  |  | <b>4</b>    |
| <b>Foreword</b> .....   |  | <b>5</b>    |
| <b>Introduction</b> .....   |  | <b>6</b>    |
| <b>1 Scope</b> .....  |  | <b>7</b>    |
| <b>2 Normative references</b> .....   |  | <b>7</b>    |
| <b>3 Terms and definitions</b> .....  |  | <b>7</b>    |
| <b>4 Instrumentation</b> .....  |  | <b>11</b>   |
| 4.1 General.....  |  | 11          |
| 4.2 Calibration.....  |  | 11          |
| 4.3 Verification.....   |  | 11          |
| <b>5 Frequency range</b> .....  |  | <b>12</b>   |
| 5.1 Tapping machine as the impact source.....   |  | 12          |
| 5.2 Rubber ball as the impact source.....   |  | 12          |
| <b>6 General</b> .....  |  | <b>12</b>   |
| <b>7 Default procedure for sound pressure level measurement</b> .....                       |  | <b>13</b>   |
| 7.1 General.....  |  | 13          |
| 7.2 Generation of sound field.....  |  | 13          |
| 7.2.1 General.....  |  | 13          |
| 7.2.2 Impact source positions for the tapping machine as impact source.....                 |  | 13          |
| 7.2.3 Impact source positions for the rubber ball as impact source.....                     |  | 14          |
| 7.3 Fixed microphone positions for the tapping machine or rubber ball as impact source..... |  | 14          |
| 7.3.1 General.....  |  | 14          |
| 7.3.2 Number of measurements.....   |  | 14          |
| 7.3.3 Tapping machine operated at more than one position.....                               |  | 14          |
| 7.3.4 Rubber ball operated at more than one position.....                                   |  | 15          |
| 7.4 Mechanized continuously moving microphone for the tapping machine as impact source..... |  | 15          |
| 7.4.1 General.....  |  | 15          |
| 7.4.2 Number of measurements.....   |  | 16          |
| 7.4.3 Tapping machine operated at more than one position.....                               |  | 16          |
| 7.5 Manually scanned microphone for the tapping machine as impact source.....               |  | 16          |
| 7.5.1 General.....  |  | 16          |
| 7.5.2 Number of measurements.....   |  | 16          |
| 7.5.3 Tapping machine operated at more than one position.....                               |  | 16          |
| 7.5.4 Circle.....   |  | 16          |
| 7.5.5 Helix.....  |  | 16          |
| 7.5.6 Cylindrical-type.....   |  | 17          |
| 7.5.7 Three semicircles.....  |  | 17          |
| 7.6 Minimum distances for microphone positions.....   |  | 18          |
| 7.7 Averaging times for the tapping machine as impact source.....                           |  | 18          |
| 7.7.1 Fixed microphone positions.....   |  | 18          |
| 7.7.2 Mechanized continuously moving microphone.....  |  | 19          |
| 7.7.3 Manually scanned microphone.....  |  | 19          |

|           |   |           |
|-----------|---|-----------|
| 7.8       | Calculation of energy-average sound pressure levels.....  | 19        |
| 7.8.1     | Fixed microphone positions for the tapping machine as impact source.....  | 19        |
| 7.8.2     | Mechanized continuously moving microphone and manually scanned microphone for the tapping machine as impact source..... | 19        |
| 7.8.3     | Fixed microphone positions for the rubber ball as impact source.....  | 20        |
| <b>8</b>  | <b>Low-frequency procedure for sound pressure level measurement for the tapping machine as impact source.....</b>       | <b>20</b> |
| 8.1       | General.....  | 20        |
| 8.2       | Generation of sound field.....  | 20        |
| 8.2.1     | General.....  | 20        |
| 8.2.2     | Impact source positions.....  | 20        |
| 8.3       | Microphone positions.....   | 20        |
| 8.4       | Averaging time.....   | 21        |
| 8.5       | Calculation of low-frequency energy-average impact sound pressure levels.....   | 21        |
| <b>9</b>  | <b>Background noise (default and low-frequency procedure).....</b>  | <b>22</b> |
| 9.1       | General.....  | 22        |
| 9.2       | Correction to the signal level for background noise.....  | 23        |
| <b>10</b> | <b>Reverberation time in the receiving room (default and low-frequency procedure).....</b>                              | <b>24</b> |
| 10.1      | General.....  | 24        |
| 10.2      | Generation of sound field.....  | 24        |
| 10.3      | Default procedure.....  | 24        |
| 10.4      | Low-frequency procedure.....  | 24        |
| 10.5      | Interrupted noise method.....   | 25        |
| 10.6      | Integrated impulse response method.....   | 25        |
| <b>11</b> | <b>Conversion to octave bands.....</b>  | <b>25</b> |
| <b>12</b> | <b>Expression of results.....</b>   | <b>26</b> |
| <b>13</b> | <b>Uncertainty.....</b>   | <b>26</b> |
| <b>14</b> | <b>Test report.....</b>   | <b>26</b> |
|           | <b>Annex A (normative) Impact sources.....</b>  | <b>28</b> |
|           | <b>Annex B (normative) Requirements for loudspeakers used for reverberation time measurements.....</b>                  | <b>34</b> |
|           | <b>Annex C (informative) Forms for the expression of results.....</b>   | <b>35</b> |
|           | <b>Annex D (informative) Additional guidance.....</b>   | <b>39</b> |
|           | <b>Annex E (informative) Horizontal measurements — Examples of suitable impact source and microphone positions.....</b> | <b>43</b> |
|           | <b>Annex F (informative) Vertical measurements — Examples of suitable impact source and microphone positions.....</b>   | <b>47</b> |
|           | <b>Bibliography.....</b>  | <b>50</b> |