

DIN EN ISO 7779:2019-04 (E)

Acoustics - Measurement of airborne noise emitted by information technology and telecommunications equipment (ISO 7779:2018)

Contents		Page
EN ISO 7779:2018 (E) European foreword		6
Foreword		7
Introduction		9
1	Scope	10
2	Normative references	10
3	Terms and definitions	11
3.1	General definitions	11
3.2	Acoustical definitions	13
3.3	Statistical definitions	16
4	Conformity requirements	16
5	Installation and operating conditions	17
5.1	Equipment installation	17
5.1.1	General	17
5.1.2	Floor-standing equipment	17
5.1.3	Table-top equipment	18
5.1.4	Wall-mounted equipment	18
5.1.5	Rack-mounted equipment	18
5.1.6	Hand-held equipment	18
5.1.7	Sub-assemblies	18
5.2	Input voltage and frequency	19
5.3	Equipment operation	19
6	Method for determination of sound power levels of equipment in reverberation test rooms	20
6.1	General	20
6.2	Measurement uncertainty	20
6.3	Test environment	21
6.3.1	General	21
6.3.2	Meteorological conditions	21
6.4	Instrumentation	21
6.4.1	General	21
6.4.2	The microphone and its associated cable	21
6.4.3	Frequency response of the instrumentation system	21
6.4.4	Reference sound source	22
6.4.5	Filter characteristics	22
6.4.6	Calibration	22
6.5	Installation and operation of equipment: general requirements	22
6.6	Microphone positions and source locations	22
6.6.1	General	22
6.6.2	Number of microphone positions, reference sound source locations and equipment locations	23
6.6.3	Microphone arrangement	23
6.7	Measurement of sound pressure level	23

DIN EN ISO 7779:2019-04 EN ISO 7779:2018 (E) 6.7.1	General	23
6.7.2	Measurement duration	23
6.7.3	Corrections for background noise	23
6.8	Measurement of the sound pressure level of the reference sound source	23
6.9	Calculation of mean time-averaged band sound pressure level	23
6.10	Determination of sound power level	23
6.10.1	Calculation of band sound power levels	23
6.10.2	Calculation of A-weighted sound power level	24
7	Method for determination of sound power levels of equipment under essentially free-field conditions over a reflecting plane	26
7.1	General	26
7.2	Measurement uncertainty	26
7.3	Test environment	27
7.3.1	Essentially free field over a reflecting plane	27
7.3.2	Meteorological conditions	28
7.4	Instrumentation	29
7.4.1	General	29
7.4.2	The microphone and its associated cable	29
7.4.3	Frequency response of the instrumentation system	29
7.4.4	Reference sound source	29
7.4.5	Filter characteristics	29
7.4.6	Calibration	29
7.5	Installation and operation of equipment: General requirements	29
7.6	Measurement surface and microphone positions	30
7.6.1	General	30
7.6.2	Microphone positions on the measurement surface	31
7.7	Measurement of sound pressure levels	31
7.7.1	General	31
7.7.2	Measurement duration	31
7.7.3	Corrections for background noise	31
7.8	Calculation of surface sound pressure level	31
7.9	Determination of sound power levels	32
7.9.1	Calculation of band sound power levels	32
7.9.2	Calculation of A-weighted sound power level	32
8	Method for determination of emission sound pressure levels at defined operator and bystander positions	32
8.1	General	32
8.2	Measurement uncertainty	33
8.3	Test environment	33
8.3.1	General	33
8.3.2	Meteorological conditions	33
8.4	Instrumentation	34
8.5	Installation and operation of equipment	34
8.6	Microphone positions	34
8.6.1	General	34
8.6.2	At the operator position(s)	34
8.6.3	At the bystander positions	37
8.6.4	Microphone orientation	37
8.7	Measurement of sound pressure levels	37
8.7.1	General	37
8.7.2	Measurement duration	38
8.7.3	Corrections for background noise	38
DIN EN ISO 7779:2019-04 EN ISO 7779:2018 (E) 8.8	Determination of emission sound pressure levels	38
8.8.1	Calculation of band emission sound pressure levels	38
8.8.2	Calculation of A-weighted emission sound pressure levels from band levels	38
8.8.3	Calculation of the mean emission sound pressure level at the bystander positions	39
9	Measurement uncertainty	39

10	Information to be recorded and reported	41
10.1	Information to be recorded	41
10.1.1	General	41
10.1.2	Equipment under test	41
10.1.3	Acoustical environment	41
10.1.4	Instrumentation	42
10.1.5	Acoustical data	43
10.2	Test report	44
Annex A (normative) Test accessories		46
A.1	Standard test table	46
A.2	Typing robot	46
Annex B (normative) Measurement surfaces		49
B.1	Hemispherical measurement surface	49
B.2	Cylindrical measurement surface	49
B.2.1	General	49
B.2.2	Selection of size of cylindrical measurement surface	50
B.2.3	Selection of microphone positions on the cylindrical measurement surface	50
B.2.4	Calculation of the mean time-averaged sound pressure level over the cylindrical measurement surface	52
Annex C (normative) Installation and operating conditions for specific equipment categories		55
Annex D (informative) Identification and evaluation of prominent discrete tones		56
D.1	Scope	56
D.2	Annex status	56
D.3	Psychoacoustical background	56
D.4	Microphone position(s)	57
D.5	Instrumentation	57
D.6	Initial screening tests	58
D.6.1	General	58
D.6.2	Screening test for audibility of discrete tone(s) in noise generally well above the threshold of hearing	58
D.6.3	Screening test for audibility of discrete tone(s) in noise near the threshold of hearing	58
D.7	Discrete tones and noise emissions near the threshold of hearing	59
D.7.1	Lower threshold of hearing	59
D.7.2	Normalization of noise near threshold of hearing	60
D.8	Critical bandwidths	61
D.9	Tone-to-noise ratio method	62
D.9.1	Measurement using FFT analyser	62
D.9.2	Determination of discrete tone level	62
D.9.3	Determination of masking noise level	62
D.9.4	Determination of the tone-to-noise ratio	63
D.9.5	Prominent discrete tone criteria for tone-to-noise ratio method	63
D.9.6	Multiple tones in a critical band	64
D.9.7	Complex tones containing harmonic components (tone-to-noise ratio method)	65
DIN EN ISO 7779:2019-04 EN ISO 7779:2018 (E) D.9.8 Audibility requirements		65
D.9.9	Example (tone-to-noise ratio method)	65
D.10	Prominence ratio method	66
D.10.1	Measurement using FFT analyser	66
D.10.2	Determination of the level of the middle critical band	69
D.10.3	Determination of the level of the lower critical band	69
D.10.4	Determination of the level of the upper critical band	70
D.10.5	Determination of prominence ratio	71
D.10.6	Prominent discrete tone criterion for prominence ratio method	71
D.10.7	Complex tones containing harmonic components (prominence ratio method)	72

D.10.8	Audibility requirements	72
D.10.9	Example (prominence ratio method)	72
D.11	Information to be recorded for prominent discrete tones	74
Annex E (informative) Background information on the method formerly used for the detection of impulsive noise		76
Bibliography		77