

ISO 4869-2:2018 (E)

Acoustics — Hearing protectors — Part 2: Estimation of effective A-weighted sound pressure levels when hearing protectors are worn

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Measurement of sound attenuation of hearing protectors
5	Calculation of the assumed protection value, APV _{fx} , of a hearing protector for a selected protection performance
6	Octave-band method
7	HML method
7.1	General
7.2	Calculation of H, M and L values
7.3	Application of HML method for estimation of the effective A-weighted sound pressure level
8	SNR method
8.1	General
8.2	Calculation of SNR values
8.3	Application of SNR method for estimation of the effective A-weighted sound pressure level
Annex A	(informative) Example of the calculation of the assumed protection values, APV _{fx}
Annex B	(informative) Example of the calculation of L' _{p,Ax} according to the octave-band method
Annex C	(informative) Example of the calculation and use of H, M and L values
C.1	Calculation of H, M and L values for a particular hearing protector
C.2	Use of H ₈₄ , M ₈₄ and L ₈₄ values to estimate L' _{p,A84} for a particular hearing protector in a specific noise situation
Annex D	(informative) Example of the calculation and use of SNR values
D.1	Calculation of the SNR value for a particular hearing protector
D.2	Use of the SNR ₈₄ value to estimate L' _{p,A84} for a particular hearing protector in a specific noise situation for which L _{p,C} is known
D.3	Use of the SNR ₈₄ value to estimate L' _{p,A84} for a particular hearing protector in a specific noise situation in which the A-weighted sound pressure level has been measured and a reasonable estimate of (L _{p,C} – L _{p,A}) is available
Annex E	(informative) Uncertainty of attenuation values and ratings
E.1	General
E.2	Example of uncertainty