

ISO 13473-1:2019 (E)

Characterization of pavement texture by use of surface profiles — Part 1: Determination of mean profile depth

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Test surfaces
4.1	Condition of the surface
4.2	Amount of data to be collected per field test section
4.2.1	Continuous measurements
4.2.2	Spot measurements
4.3	Amount of data to be collected on laboratory samples
5	Measurement instruments
5.1	Instruments in general
5.2	Vertical resolution
5.3	Horizontal resolution
5.4	Measurement speed
5.5	Alignment of sensor
5.6	Bandwidth of sensor and recording system
5.7	Performance check
5.8	Indication of invalid readings (drop-outs)
5.9	Sensitivity to vibrations
6	Measurement procedure
6.1	Performance checks
6.2	Measurements
6.3	Continuous or spot measurements
7	Data processing procedure
7.1	General
7.2	Summary of data processing steps
7.3	Drop-out correction and interpolation
7.4	Resampling to a certain spatial resolution
7.5	Spike identification and reshaping the profile
7.6	Removal of long-wavelength components and normalization of profile sharpness
7.7	Segment limiting
7.8	Peak and MSD determination
7.9	Extreme MSD value removal (optional)
7.10	Averaging of MSD to determine the MPD
7.11	Calculation of ETD (optional)
8	Measurement uncertainty assessment according to ISO/IEC Guide 98-3
9	Safety considerations
10	Test report
Annex A	(informative) Texture ranges

Annex B (informative) Problems experienced on special surfaces

- B.1 Porous surfaces**
- B.2 Newly laid surfaces and humid/wet surfaces**
- B.3 Surfaces with directional finish (e.g. grooved, ground or tined concrete)**

Annex C (informative) Procedure for sampling of mean segment depth values by spot measurements

- C.1 Background**
- C.2 Procedure**
 - C.2.1 General**
 - C.2.2 Case 1: Lane length L is shorter than 1 000 m ($L \leq 1\,000$ m)**
 - C.2.3 Case 2: Lane length L is longer than 1 000 m ($L > 1\,000$ m)**
 - C.2.4 Example illustrating Case 2**

Annex D (normative) Data quality-enhancing procedures

- D.1 General**
- D.2 Summary of the specified data processing procedures**
- D.3 Brief description of the procedures**
 - D.3.1 Drop-out identification (mandatory)**
 - D.3.2 Maximum use of data (mandatory where applicable)**
 - D.3.3 Spike identification (mandatory)**
 - D.3.4 Reshape profile (space domain, mandatory)**
 - D.3.5 Removal of slope and long-wavelength components (mandatory)**
 - D.3.6 Normalization of sharpness by low-pass filtering (space domain, mandatory)**
 - D.3.7 Extreme MSD value removal (space domain, optional, only for MSD determination)**
- D.4 Aid in designing the filters**

Annex E (normative) Spike removal procedure

- E.1 General**
- E.2 Example**

Annex F (informative) Measurement uncertainty

- F.1 General**
- F.2 Expression for the calculation of the MPD value**
- F.3 Sources of uncertainty**
- F.4 Estimation of uncertainties of the method**

Annex G (informative) Performance check

Annex H (informative) Flow charts for determination of MSD and MPD

Page count: 43