

DIN EN ISO 3743-2:2022-11 (E)

Acoustics - Determination of sound power levels of noise sources using sound pressure - Engineering methods for small, movable sources in reverberant fields - Part 2: Methods for special reverberation test rooms (ISO 3743-2:2018)

| Contents | | Page |
|---|---|-------------|
| European foreword | | 4 |
| Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2006/42/EC aimed to be covered | | 5 |
| Foreword | | 6 |
| Introduction | | 7 |
| 1 | Scope | 8 |
| 2 | Normative references | 8 |
| 3 | Terms and definitions | 8 |
| 4 | Principle | 9 |
| 5 | Noise source | 9 |
| 6 | Requirements for special reverberation test room | 9 |
| 6.1 | General | 9 |
| 6.2 | Volume of test room | 9 |
| 6.3 | Reverberation time of test room | 10 |
| 6.4 | Surface treatment | 10 |
| 6.5 | Criterion for background noise | 10 |
| 6.6 | Criteria for temperature and humidity | 11 |
| 6.7 | Evaluation of suitability of test room | 11 |
| 7 | Instrumentation | 12 |
| 7.1 | General | 12 |
| 7.2 | Microphone and its associated cable | 12 |
| 7.3 | Amplifier and weighting network | 13 |
| 7.4 | Octave-band filters | 13 |
| 7.5 | Squaring and averaging circuits and indicating device | 13 |
| 7.6 | Frequency response of the instrumentation system | 13 |
| 7.7 | Calibration | 13 |
| 8 | Installation and operation of source under test | 14 |
| 8.1 | General | 14 |
| 8.2 | Source location | 14 |
| 8.3 | Source mounting | 14 |
| 8.4 | Auxiliary equipment | 14 |
| 8.5 | Operation of source during the test | 14 |
| 9 | Measurements in test room | 15 |
| 9.1 | General | 15 |
| 9.2 | Period of observation | 15 |
| 9.3 | Microphone positions | 15 |
| 9.4 | Number of microphones and source positions | 16 |

| | | |
|--|--|----|
| 9.5 | Criteria for the presence of spectral irregularities | 17 |
| 9.6 | Averaging technique with moving microphones | 17 |
| 9.6.1 | General | 17 |
| 9.6.2 | Path length for continuous averaging | 18 |
| 9.6.3 | Location of path within test room | 18 |
| 9.6.4 | Speed of traverse | 18 |
| 9.7 | Array of fixed microphones | 18 |
| 9.8 | Correction for background sound pressure levels | 18 |
| 10 | Calculation of sound power levels | 19 |
| 10.1 | Calculation of mean band pressure levels | 19 |
| 10.2 | Direct method for determining sound power levels | 19 |
| 10.3 | Comparison method for determining band power levels | 20 |
| 10.4 | A-weighted sound power levels determined by the comparison method | 21 |
| 11 | Measurement uncertainty | 21 |
| 11.1 | Methodology | 21 |
| 11.2 | Determination of σ_{mc} | 22 |
| 11.3 | Determination of R_0 | 22 |
| 11.3.1 | General | 22 |
| 11.3.2 | Round robin test | 22 |
| 11.3.3 | Modelling approach for R_0 | 23 |
| 11.4 | Typical upper bound values of R_0 | 23 |
| 11.5 | Total standard deviation σ_{tot} and expanded uncertainty U | 24 |
| 12 | Information to be recorded | 24 |
| 12.1 | General | 24 |
| 12.2 | Sound source under test | 24 |
| 12.3 | Acoustical environment | 25 |
| 12.4 | Instrumentation | 25 |
| 12.5 | Acoustical data | 25 |
| 13 | Information to be reported | 25 |
| Annex A (normative) Characteristics and calibration of reference sound source | | 26 |
| Annex B (informative) Guidelines for the design of special reverberation test rooms | | 27 |
| Annex C (informative) Examples of suitable instrumentation systems | | 32 |
| Annex D (informative) Guidance on the development of information on measurement uncertainty .. | | 34 |
| Annex E (normative) Sound power level under reference meteorological conditions | | 44 |
| Annex F (normative) Calculation of A-weighted sound power levels from octave band levels | | 45 |
| Bibliography | | 46 |