

DIN EN ISO 16283-2:2020-11 (Englisch)

Acoustics - Field measurement of sound insulation in buildings and of building elements - Part 2: Impact sound insulation (ISO 16283-2:2020)

| Contents | | Page |
|--|--|-------------|
| European foreword | | 4 |
| Foreword | | 5 |
| Introduction | | 6 |
| 1 Scope | | 7 |
| 2 Normative references | | 7 |
| 3 Terms and definitions | | 7 |
| 4 Instrumentation | | 11 |
| 4.1 General | | 11 |
| 4.2 Calibration | | 11 |
| 4.3 Verification | | 11 |
| 5 Frequency range | | 12 |
| 5.1 Tapping machine as the impact source | | 12 |
| 5.2 Rubber ball as the impact source | | 12 |
| 6 General | | 12 |
| 7 Default procedure for sound pressure level measurement | | 13 |
| 7.1 General | | 13 |
| 7.2 Generation of sound field | | 13 |
| 7.2.1 General | | 13 |
| 7.2.2 Impact source positions for the tapping machine as impact source | | 13 |
| 7.2.3 Impact source positions for the rubber ball as impact source | | 14 |
| 7.3 Fixed microphone positions for the tapping machine or rubber ball as impact source | | 14 |
| 7.3.1 General | | 14 |
| 7.3.2 Number of measurements | | 14 |
| 7.3.3 Tapping machine operated at more than one position | | 14 |
| 7.3.4 Rubber ball operated at more than one position | | 15 |
| 7.4 Mechanized continuously moving microphone for the tapping machine as impact source | | 15 |
| 7.4.1 General | | 15 |
| 7.4.2 Number of measurements | | 16 |
| 7.4.3 Tapping machine operated at more than one position | | 16 |
| 7.5 Manually scanned microphone for the tapping machine as impact source | | 16 |
| 7.5.1 General | | 16 |
| 7.5.2 Number of measurements | | 16 |
| 7.5.3 Tapping machine operated at more than one position | | 16 |
| 7.5.4 Circle | | 16 |
| 7.5.5 Helix | | 16 |
| 7.5.6 Cylindrical-type | | 17 |
| 7.5.7 Three semicircles | | 17 |
| 7.6 Minimum distances for microphone positions | | 18 |
| 7.7 Averaging times for the tapping machine as impact source | | 18 |
| 7.7.1 Fixed microphone positions | | 18 |
| 7.7.2 Mechanized continuously moving microphone | | 19 |
| 7.7.3 Manually scanned microphone | | 19 |
| 7.8 Calculation of energy-average sound pressure levels | | 19 |
| 7.8.1 Fixed microphone positions for the tapping machine as impact source | | 19 |
| 7.8.2 Mechanized continuously moving microphone and manually scanned microphone for the tapping machine as impact source | | 19 |
| 7.8.3 Fixed microphone positions for the rubber ball as impact source | | 20 |

| | | |
|-----------|--|-----------|
| 8 | Low-frequency procedure for sound pressure level measurement for the tapping machine as impact source | 20 |
| 8.1 | General..... | 20 |
| 8.2 | Generation of sound field..... | 20 |
| | 8.2.1 General..... | 20 |
| | 8.2.2 Impact source positions | 20 |
| 8.3 | Microphone positions..... | 20 |
| 8.4 | Averaging time | 21 |
| 8.5 | Calculation of low-frequency energy-average impact sound pressure levels | 21 |
| 9 | Background noise (default and low-frequency procedure) | 22 |
| 9.1 | General..... | 22 |
| 9.2 | Correction to the signal level for background noise..... | 23 |
| 10 | Reverberation time in the receiving room (default and low-frequency procedure) | 24 |
| 10.1 | General..... | 24 |
| 10.2 | Generation of sound field..... | 24 |
| 10.3 | Default procedure..... | 24 |
| 10.4 | Low-frequency procedure..... | 24 |
| 10.5 | Interrupted noise method..... | 25 |
| 10.6 | Integrated impulse response method..... | 25 |
| 11 | Conversion to octave bands | 25 |
| 12 | Expression of results | 26 |
| 13 | Uncertainty | 26 |
| 14 | Test report | 26 |
| | Annex A (normative) Impact sources | 27 |
| | Annex B (normative) Requirements for loudspeakers used for reverberation time measurements | 33 |
| | Annex C (informative) Forms for the expression of results | 34 |
| | Annex D (informative) Additional guidance | 38 |
| | Annex E (informative) Horizontal measurements — Examples of suitable impact source and microphone positions | 42 |
| | Annex F (informative) Vertical measurements — Examples of suitable impact source and microphone positions | 46 |
| | Bibliography | 49 |