

ISO 10140-5:2021 (E)

Acoustics — Laboratory measurement of sound insulation of building elements — Part 5: Requirements for test facilities and equipment

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Laboratory test facilities for airborne sound insulation measurements
4.1	General
4.2	Test rooms
4.2.1	Volume
4.2.2	Diffusion
4.2.3	Reverberation time
4.2.4	Background noise
4.2.5	Suppression of flanking transmission
4.3	Test opening
4.3.1	General
4.3.2	Full-sized test opening
4.3.2.1	General
4.3.2.2	General frame specification
4.3.2.3	Specific requirements on the frame for lightweight double-leaf partitions
4.3.3	Reduced-size test opening
4.3.4	Specific small-sized test opening
5	Laboratory test facilities for impact sound insulation measurements
5.1	General
5.2	Receiving room
5.2.1	Volume
5.2.2	Further requirements
5.3	Test opening
5.3.1	Full-sized test opening
5.3.2	Frame specification
6	Equipment
6.1	Airborne sound field
6.2	Impact sound source
6.3	Measurement system
Annex A	(normative) Estimation of the maximum measurable sound reduction index
A.1	General
A.2	Qualification procedures and requirements
A.2.1	Maximum measurable sound reduction index — R'_{max} facility
A.2.2	Representative constructions
A.2.2.1	Walls
A.2.2.1.1	Type A: Lightweight wall
A.2.2.1.2	Type B: Lightweight masonry wall
A.2.2.1.3	Type C: Heavyweight masonry wall
A.2.2.2	Floors
A.2.2.2.1	Type A: Lightweight floor
A.2.2.2.2	Type B: Lightweight concrete floor

A.2.2.2.3 Type C: Heavyweight concrete floor

Annex B (normative) Standard basic elements for measuring the improvement of airborne sound insulation by linings

- B.1 Standard basic elements**
- B.2 Standard wall with low critical frequency (“heavy wall”)**
- B.3 Standard floor with low critical frequency (“heavy floor”)**
- B.4 Standard wall with medium critical frequency (“lightweight wall”)**

Annex C (normative) Standard floors for measuring the improvement of impact sound insulation by floor coverings

- C.1 Standard reference elements**
- C.2 Heavyweight reference floor**
 - C.2.1 General**
 - C.2.2 Condition of floor surface**
- C.3 Lightweight reference floors**
 - C.3.1 General**
 - C.3.2 Condition of floor surface**
 - C.3.3 Types of lightweight reference floors**
 - C.3.3.1 General**
 - C.3.3.2 Lightweight reference floor of type No 1**
 - C.3.3.3 Lightweight reference floor of type No 2**
 - C.3.3.4 Lightweight reference floor of type No 3**

Annex D (normative) Qualification procedure for loudspeakers and loudspeaker positions

- D.1 Test procedure to find the number of source positions and the optimal positions**
 - D.1.1 General**
 - D.1.2 Requirements for loudspeaker positions in the selection procedure**
 - D.1.3 Guidelines for finding optimal positions and qualification test**
 - D.1.4 Test element**
 - D.1.5 Use of continuously moving loudspeakers**
- D.2 Test procedure for loudspeaker radiation directivity**
- D.3 Test procedure for loudspeaker positions with regard to microphone positions**

Annex E (normative) Standard tapping machine

- E.1 Requirements**
- E.2 Regular checks of performance**

Annex F (normative) Alternative impact sound sources

- F.1 Modified tapping machine**
 - F.1.1 General**
 - F.1.2 Method A**
 - F.1.3 Method B**
- F.2 Heavy/soft impact source — Rubber ball**
 - F.2.1 General**
 - F.2.2 Impact force characteristics**
 - F.2.3 Example of the construction of the heavy/soft impact source**

Annex G (normative) Wooden mock-up floor for measuring the improvement of impact sound insulation by floor coverings

- G.1 Alternative basic element**
- G.2 Lightweight top floor**

Annex H (normative) Specification of heavy and intense rain — Example of a tank with perforated base

- H.1 Specification of artificial rain production**
- H.2 Rain production for generation of artificial raindrops**
 - H.2.1 General**
 - H.2.2 Artificial raindrop generation system**
 - H.2.3 Calibration of the raindrop generation system**

Annex I (informative) Reference test specimens for rainfall sound measurements

- I.1 General**
- I.2 Small test specimen**
- I.3 Large test specimen**