

# ISO 8041-2:2021 (E)

## Human response to vibration — Measuring instrumentation — Part 2: Personal vibration exposure meters

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Reference environmental conditions
5	Performance specifications
5.1	General characteristics
5.1.1	Common characteristics
5.1.2	Special characteristics for whole-body vibration measurement
5.1.3	Special characteristics for hand-arm vibration measurement
5.2	Display
5.3	Electrical output
5.4	Vibration sensitivity
5.5	Accuracy of indication at reference frequency under reference conditions
5.6	Frequency weightings and frequency responses
5.6.1	Parameters
5.6.2	Band-limiting filter
5.6.3	a-v transition filter
5.6.4	Upward-step filter
5.6.5	Overall frequency weighting
5.6.6	Tolerances
5.7	Amplitude linearity
5.8	Instrument noise
5.9	Signal#burst response
5.10	Overload indication
5.11	Under#range indication
5.12	Time averaging
5.13	Running RMS acceleration
5.14	Clearance of data and instrument state (named reset)
5.15	Timing facilities
5.16	Electrical cross-talk
5.17	Vibration transducer characteristics
5.18	Power supply
5.19	Operator detection system
5.20	Detection of transient acceleration artefacts
5.21	Logging capabilities
5.22	Contact force measurement
5.23	Warning indication
5.23.1	General
5.23.2	Mandatory warning indications
5.23.3	Optional warning indications
5.24	Human interface and ergonomic aspects
6	Mounting
7	Environmental and electromagnetic criteria

- 7.1 General
- 7.2 Air temperature
- 7.3 Surface temperature
- 7.4 Electrostatic discharge
- 7.5 Radio-frequency emissions and public-power-supply disturbances
- 7.6 Immunity to AC power-frequency fields and radio-frequency fields
- 7.7 Ingress of water and dust
- 8 Provision for use with auxiliary devices
- 9 Instrument marking
- 10 Instrument documentation
- 11 Performance testing
- 12 Pattern evaluation
  - 12.1 General
  - 12.2 Testing requirements
  - 12.3 Submission for testing
  - 12.4 Marking of the instrument and information in the instrument documentation
  - 12.5 Mandatory facilities and general requirements
  - 12.6 Initial instrument preparation
  - 12.7 Indication at the reference frequency under reference conditions
  - 12.8 Electrical cross-talk
  - 12.9 Vibration transducer
  - 12.10 Amplitude linearity
    - 12.10.1 Electrical tests of amplitude linearity
    - 12.10.2 Mechanical tests of amplitude linearity
  - 12.11 Frequency weightings and frequency responses
    - 12.11.1 General
    - 12.11.2 Mechanical tests of frequency response
    - 12.11.3 Electrical tests of frequency response
    - 12.11.4 Conformance
  - 12.12 Instrument noise
  - 12.13 Signal-burst response
  - 12.14 Overload indication
  - 12.15 Reset
  - 12.16 Combined axis outputs
  - 12.17 AC electrical output
  - 12.18 Timing facilities
  - 12.19 Power supply
  - 12.20 Environmental, electrostatic and radio-frequency tests
    - 12.20.1 General
    - 12.20.2 Expanded uncertainties for measurements of environmental conditions
    - 12.20.3 Acclimatization requirements for tests of the influence of air temperature and relative humidity
    - 12.20.4 Test of the influence of air temperature and relative humidity combined
    - 12.20.5 Influence of surface temperature
    - 12.20.6 Influence of electrostatic discharges
    - 12.20.7 Radio-frequency emissions and public-power-supply disturbances
    - 12.20.8 Immunity to AC power-frequency fields and radio-frequency fields
  - 12.21 Operator detection system
  - 12.22 Logging capabilities
  - 12.23 Warning indication (mandatory warnings)
  - 12.24 Test report
- 13 Periodic verification
  - 13.1 General
  - 13.2 Testing requirements
  - 13.3 Test object
  - 13.4 Submission for testing
  - 13.5 Preliminary inspection
  - 13.6 Marking of the instrument and information in the instrument documentation

13.7	Test procedure
13.8	Test parameters
13.8.1	Vibration measurement chain for hand-arm vibration
13.8.2	Vibration measurement chain for whole-body vibration
13.8.3	Vibration measurement chain low-frequency whole-body vibration
13.9	Conducting the test
13.10	Test report
14	In-situ check
14.1	General
14.2	Preliminary inspection
14.3	Vibration sensitivity (field calibration)
Annex A	(informative) Treatment of transient acceleration artefacts
A.1	Identifying and dealing with artefacts
A.2	Principles of artefact treatment
A.3	Treatment of artefacts
A.3.1	General
A.3.2	Cutting out the artefact
A.3.3	Linearizing the artefact
A.3.4	Substituting the artefact
A.4	Example of hand-arm artefact treatment
A.5	Example of whole-body artefact treatment
Annex B	(informative) Influence of coupling force on hand-arm vibration evaluation
B.1	General
B.2	Measurement of coupling forces
Annex C	(informative) Human interface

Page count: 53