

# ISO 10326-2:2022-03 (E)

## Mechanical vibration - Laboratory method for evaluating vehicle seat vibration - Part 2: Application to railway vehicles

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions, symbols and abbreviated terms .....</b>	<b>1</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.2</b>	<b>Symbols and abbreviated terms .....</b>	<b>2</b>
<b>4</b>	<b>Direction of vibration .....</b>	<b>3</b>
<b>5</b>	<b>Characterization of vibration and of its transmission .....</b>	<b>4</b>
<b>5.1</b>	<b>Characterization of vibration .....</b>	<b>4</b>
<b>5.1.1</b>	<b>General .....</b>	<b>4</b>
<b>5.1.2</b>	<b>Root-mean-square acceleration, arms .....</b>	<b>4</b>
<b>5.1.3</b>	<b>Acceleration power auto spectral density, <math>G_{aa}(f)</math> .....</b>	<b>5</b>
<b>5.1.4</b>	<b>Acceleration cross spectral density, <math>G_{ab}(f)</math> .....</b>	<b>5</b>
<b>5.2</b>	<b>Characterization of vibration transmission .....</b>	<b>5</b>
<b>5.2.1</b>	<b>General .....</b>	<b>5</b>
<b>5.2.2</b>	<b>Frequency response function, <math>H(f)</math> .....</b>	<b>5</b>
<b>5.2.3</b>	<b>Coherence function, <math>ab(\ ) f</math> .....</b>	<b>5</b>
<b>5.2.4</b>	<b>Transmissibility, TR .....</b>	<b>6</b>
<b>5.2.5</b>	<b>Weighted transmissibility, TR<sub>w</sub> and SEAT factor .....</b>	<b>6</b>
<b>6</b>	<b>General observations .....</b>	<b>7</b>
<b>7</b>	<b>Measurement positions .....</b>	<b>7</b>
<b>8</b>	<b>Instrumentation .....</b>	<b>7</b>
<b>9</b>	<b>Safety requirements .....</b>	<b>8</b>
<b>10</b>	<b>Test seats and test persons .....</b>	<b>8</b>
<b>10.1</b>	<b>Test seats .....</b>	<b>8</b>
<b>10.2</b>	<b>Test persons .....</b>	<b>8</b>
<b>11</b>	<b>Input test vibration .....</b>	<b>9</b>
<b>11.1</b>	<b>General .....</b>	<b>9</b>
<b>11.2</b>	<b>Pseudo-random excitation .....</b>	<b>9</b>
<b>11.2.1</b>	<b>Generation of the excitation signal .....</b>	<b>9</b>
<b>11.2.2</b>	<b>Power auto spectral density .....</b>	<b>10</b>
<b>11.2.3</b>	<b>Root-mean-square acceleration .....</b>	<b>10</b>
<b>11.2.4</b>	<b>Tolerances .....</b>	<b>10</b>
<b>11.2.5</b>	<b>Multi-axis excitation .....</b>	<b>10</b>
<b>11.3</b>	<b>Sinusoidal excitation .....</b>	<b>10</b>
<b>11.4</b>	<b>Realistic excitation representing the dynamic environment of the tested seat .....</b>	<b>11</b>
<b>12</b>	<b>Parameters adopted for characterizing the vibration transmission .....</b>	<b>11</b>

12.1	Pseudo-random and realistic excitations .....	11
12.2	Sinusoidal excitation .....	11
13	Test procedure .....	12
13.1	Initial procedure .....	12
13.2	Tests under pseudo-random and realistic excitations .....	12
13.3	Tests under sinusoidal excitation .....	12
14	Test report .....	12
14.1	Seat .....	12
14.2	Test persons .....	12
14.3	Measuring chain .....	13
14.4	Results .....	13
Annex A (informative) Example of excitation generating process .....		16
Annex B (informative) Realistic vibration excitation for seat testing .....		19
Bibliography .....		27