ISO 10813-4:2022-04 (E)

Vibration generating machines - Guidance for selection - Part 4: Equipment for multi-axial environmental testing

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Requirements for multi-axial environmental tests 2
4.1 Multi-axial vibration test motivation 2
4.2 Test waveforms 3
4.3 Types of multi-axial environmental testing 3
4.3.1 General 3
4.3.2 Parallel thrust testing 3
4.3.3 Bi-axial vibration testing 3
4.3.4 Tri-axial vibration testing 4
4.3.5 Six-degrees-of-freedom vibration testing 4
4.3.6 Other multi-degrees-of -freedom testing 4

5 Multi-axial vibration test equipment 4
5.1 Types of multi-axial vibration test equipment 4
5.1.1 General 4
5.1.2 Parallel thrust equipment 4
5.1.3 Bi-axial linear vibration equipment 4
5.1.4 Tri-axial linear vibration equipment 6
5.1.5 Six-degrees-of-freedom test equipment 6
5.1.6 Other multi-axial test equipment 8
5.2 Coordinate system 8
5.3 Typical configurations for multi-axial testing 8

6 Main components of multi-axial test equipment 10
6.1 Exciter 10
6.2 Table 11
6.3 Connectors 12
6.3.1 General 12
6.3.2 Spherical connector 12
6.3.3 Planar connector 14
6.3.4 Orthogonal linear bearing set 15
6.3.5 Drive rod 16
6.3.6 Other connectors 17
6.4 Other components 17

7 System parameters 18
7.1 General 18
7.2 Number of exciters 18
7.3 Number of total, linear and angular degrees of freedom 18
7.4 Maximum displacement 19
7.5 Maximum velocity 19
7.6 Maximum acceleration 19

7.7 Maximum angular displacement 19
7.8 Maximum angular velocity 20
7.9 Maximum angular acceleration 20
7.10 Frequency range 21
7.11 Parasitic motion 21
7.11.1 General 21
7.11.2 Harmonic distortion 21
7.11.3 Non-uniformity ratio 22
7.11.4 Transverse motion 22

7 12 Maximum payload 23
7.13 Maximum torque 23
7.14 Table suspension stiffness 23

8 Selection procedures 23
8.1 General 23
8.2 Determination of the exciter and connector numbers 24
8.3 Determination of exciter types 24
8.3.1 General 24
8.3.2 Test waveform 24
8.3.3 Frequency range 25
8.3.4 Maximum displacement, velocity, and acceleration 25
8.3.5 Maximum force 25
8.3.6 Validation of the proposed selection 26
8.3.7 Other factors to be considered 26

Annex A (informative) Examples of selections 27

Bibliography 34