

ISO 14839-5:2022-08 (E)

Mechanical vibration - Vibration of rotating machinery equipped with active magnetic bearings - Part 5: Touch-down bearings

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 2 |
| 3 | Terms and definitions | 2 |
| 4 | General structure and components | 2 |
| 5 | Functional targets | 4 |
| 5.1 | General | 4 |
| 5.2 | Design life | 6 |
| 5.3 | Clearance requirements | 6 |
| 5.4 | Life-cycle requirements | 6 |
| 6 | Touch-down bearing design considerations | 7 |
| 6.1 | General | 7 |
| 6.2 | Trigger events | 7 |
| 6.2.1 | Overload due to abnormal process conditions | 7 |
| 6.2.2 | AMB control instability | 8 |
| 6.2.3 | Loss of power | 9 |
| 6.2.4 | Failure in the AMB system | 10 |
| 6.2.5 | Misoperation | 10 |
| 6.3 | Transportation duty | 10 |
| 6.3.1 | General | 10 |
| 6.3.2 | AMBs without permanent magnets | 11 |
| 6.3.3 | AMBs with permanent magnets | 11 |
| 6.4 | Failure modes | 12 |
| 6.4.1 | General | 12 |
| 6.4.2 | Rolling element failure modes | 12 |
| 6.4.3 | Sliding bearing failure modes | 13 |
| 6.5 | Environmental factors | 13 |
| 6.5.1 | General | 13 |
| 6.5.2 | Corrosion resistance | 13 |
| 6.5.3 | Erosion resistance, particulate contamination | 14 |
| 6.5.4 | Liquid contamination | 14 |
| 6.5.5 | Operating temperature | 14 |
| 6.5.6 | Available cooling flow | 14 |
| 6.6 | Rotordynamic modelling considerations | 14 |
| 6.6.1 | General | 14 |
| 6.6.2 | Rotor and housing modelling requirements | 14 |
| 6.6.3 | Touch-down bearing soft mount design considerations | 16 |
| 6.6.4 | Touch-down bearing clearance design considerations | 16 |
| 6.6.5 | Friction between the rotor and touch-down bearing design considerations | 16 |
| 6.7 | Contact classification/severity | 17 |
| 6.7.1 | Contact duration | 17 |
| 6.7.2 | Types of motion | 17 |
| 6.8 | Control actions following touch-down bearing contact | 19 |
| 6.8.1 | General | 19 |
| 6.8.2 | AMB controller action | 19 |

| | | |
|-------|--|----|
| 6.8.3 | Plant/variable-frequency drive control actions | 19 |
| 7 | Design and design verification | 19 |
| 7.1 | General | 19 |
| 7.2 | Design process details | 20 |
| 7.3 | Documentation | 30 |
| 8 | Condition monitoring and damage estimation methods | 30 |
| 8.1 | General | 30 |
| 8.2 | Event detection and data capture | 30 |
| 8.2.1 | Contact detection | 30 |
| 8.2.2 | Contact event | 30 |
| 8.3 | Inspection | 31 |
| 8.3.1 | General | 31 |
| 8.3.2 | Common techniques in non-intrusive inspection | 31 |
| 8.3.3 | Intrusive inspection | 32 |
| 8.4 | Damage estimation | 34 |
| 8.4.1 | Event data | 34 |
| 8.4.2 | Inspection-based estimation | 35 |
| 8.4.3 | Criteria for further operation | 36 |
| 9 | Maintenance and life cycle factors | 37 |
| 9.1 | General | 37 |
| 9.2 | Inspection plan | 37 |
| 9.2.1 | General | 37 |
| 9.2.2 | Minimum intervention cycle | 37 |
| 9.3 | Interventions | 37 |
| 9.3.1 | Routine checks | 37 |
| 9.3.2 | Predicted excessive damage accumulation | 38 |
| 9.3.3 | Contamination | 39 |
| 9.4 | Maintenance actions | 39 |
| 9.4.1 | General | 39 |
| 9.4.2 | Touch-down-bearing refurbishment | 39 |
| 9.4.3 | Touch-down bearing replacement | 40 |
| 9.5 | Life-cycle factors | 41 |
| 9.5.1 | General | 41 |
| 9.5.2 | Spare part management | 41 |
| 9.5.3 | Decommissioning, recycling and disposal | 42 |
| 9.5.4 | Obsolescence management | 42 |
| | Bibliography | 43 |