

# ISO 10534-2:2023-10 (E)

## Acoustics - Determination of acoustic properties in impedance tubes - Part 2: Two-microphone technique for normal sound absorption coefficient and normal surface impedance

---

| <b>Contents</b> |  | <b>Page</b> |
|-----------------|--|-------------|
| Foreword .....  |  | iv          |
| <b>1</b>        | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>        | <b>Normative references .....</b>  | <b>1</b>    |
| <b>3</b>        | <b>Terms, definitions and symbols .....</b>  | <b>1</b>    |
| <b>4</b>        | <b>Principle .....</b>   | <b>5</b>    |
| <b>5</b>        | <b>Test equipment .....</b>  | <b>5</b>    |
| 5.1             | Construction of the impedance tube .....   | 5           |
| 5.2             | Working frequency range .....  | 6           |
| 5.3             | Length of the impedance tube .....   | 7           |
| 5.4             | Microphones .....  | 7           |
| 5.5             | Positions of the microphones .....   | 7           |
| 5.6             | Acoustic centre of the microphone .....  | 8           |
| 5.7             | Test sample holder .....   | 8           |
| 5.8             | Signal processing equipment .....  | 9           |
| 5.9             | Loudspeaker .....  | 9           |
| 5.10            | Signal generator .....   | 9           |
| 5.11            | Thermometer, barometer and relative humidity .....                                 | 9           |
| <b>6</b>        | <b>Preliminary test and measurements .....</b>                                     | <b>10</b>   |
| <b>7</b>        | <b>Test specimen mounting .....</b>  | <b>11</b>   |
| <b>8</b>        | <b>Test procedure .....</b>  | <b>12</b>   |
| 8.1             | Specification of the reference plane .....   | 12          |
| 8.2             | Determination of the sound velocity, wavelength and characteristic impedance ..... | 12          |
| 8.3             | Selection of the signal amplitude .....  | 13          |
| 8.4             | Selection of the number of averages .....  | 13          |
| 8.5             | Correction for microphone mismatch .....   | 13          |
| 8.5.1           | General .....  | 13          |
| 8.5.2           | Measurement repeated with the channels interchanged .....                          | 13          |
| 8.5.3           | Predetermined calibration factor .....   | 14          |
| 8.6             | Determination of the transfer function between the two locations .....             | 15          |
| 8.6.1           | General .....  | 15          |
| 8.6.2           | Cross- and autospectra-based estimate .....  | 15          |
| 8.6.3           | Frequency-domain deconvolution .....   | 17          |
| 8.6.4           | Impulse-response based estimate .....  | 17          |
| 8.7             | Determination of the reflection coefficient .....                                  | 18          |
| 8.8             | Determination of the sound absorption coefficient .....                            | 18          |
| 8.9             | Determination of the specific acoustic impedance ratio .....                       | 18          |
| 8.10            | Determination of the specific acoustic admittance ratio .....                      | 18          |
| <b>9</b>        | <b>Precision .....</b>   | <b>19</b>   |
| <b>10</b>       | <b>Test report .....</b>   | <b>19</b>   |

|   |           |
|---|-----------|
| <b>Annex A (normative) Preliminary measurements .....</b>   | <b>22</b> |
| <b>Annex B (normative) Procedure for the one-microphone technique .....</b>   | <b>24</b> |
| <b>Annex C (informative) Theoretical background .....</b>   | <b>25</b> |
| <b>Annex D (informative) Error sources .....</b>  | <b>27</b> |
| <b>Annex E (informative) Estimation of diffuse sound absorption coefficient <math>\alpha</math> of locally reacting<br/>absorbers from the results of this document .....</b> | <b>29</b> |
| <b>Annex F (informative) Estimation of intrinsic properties .....</b>   | <b>30</b> |
| <b>Bibliography .....</b>   | <b>32</b> |