DIN EN 16286-2:2024-10 (E)

Railway applications - Gangway systems between vehicles - Part 2: Acoustic measurements

Contents

Page

European foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms, definitions and symbols 6
3.1 Terms and definitions 6
3.2 Symbols 13

4 Instrumentation and calibration 15
4.1 Instrumentation 15
4.2 Calibration 15

5 Test setup 15
5.1 General 15
5.2 Test setup type 1 15
5.3 Test setup type 2 16
5.4 Test setup type 3 18

6 Test procedure 19
6.1 General 19
6.2 Generation of sound field 19
6.3 Sound pressure level in the source room 19
6.4 Measurement of average sound intensity level on the measurement surface 20
6.4.1 General 20
6.4.2 Measurement surface 20
6.4.3 Qualification of the measurement surface 20
6.4.4 Scanning procedure 21
6.4.5 Procedure using discrete positions 22
6.4.6 Scanning procedure for one measurement area 22
6.4.7 Scanning procedure for a partial measurement surface Smc 22
6.5 Background noise 23
6.6 Frequency range of measurements 23

7 Presentation of results 23

8 Quality of the measurements 23
8.1 Deviations from the requirements 23
8.2 Measurement uncertainties 23

9 Test report 24

Annex A (normative) Method to qualify the sound field on the surface of the test specimen in the source room 25

Figure A.1 -- Possible setup to achieve a constant distance of 10 mm 25

Table A.1 -- Maximum acceptable deviation values Lc 26

Bibliography 27