

DIN EN 16286-2:2024-10 (E)

Railway applications - Gangway systems between vehicles - Part 2: Acoustic measurements

Contents		Page
European foreword		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Terms, definitions and symbols	6
3.1	Terms and definitions	6
3.2	Symbols	13
4	Instrumentation and calibration	15
4.1	Instrumentation	15
4.2	Calibration	15
5	Test setup	15
5.1	General	15
5.2	Test setup type 1	15
5.3	Test setup type 2	16
5.4	Test setup type 3	18
6	Test procedure	19
6.1	General	19
6.2	Generation of sound field	19
6.3	Sound pressure level in the source room	19
6.4	Measurement of average sound intensity level on the measurement surface	20
6.4.1	General	20
6.4.2	Measurement surface	20
6.4.3	Qualification of the measurement surface	20
6.4.4	Scanning procedure	21
6.4.5	Procedure using discrete positions	22
6.4.6	Scanning procedure for one measurement area	22
6.4.7	Scanning procedure for a partial measurement surface S_{mc}	22
6.5	Background noise	23
6.6	Frequency range of measurements	23
7	Presentation of results	23
8	Quality of the measurements	23
8.1	Deviations from the requirements	23
8.2	Measurement uncertainties	23
9	Test report	24
Annex A (normative) Method to qualify the sound field on the surface of the test specimen in the source room		25
Figure A.1 -- Possible setup to achieve a constant distance of 10 mm		25
Table A.1 -- Maximum acceptable deviation values L_c		26
Bibliography		27