

# DIN EN 16286-2:2024-10 (E)

## Railway applications - Gangway systems between vehicles - Part 2: Acoustic measurements

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
Introduction .....		4
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms, definitions and symbols .....</b>	<b>6</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>6</b>
<b>3.2</b>	<b>Symbols .....</b>	<b>13</b>
<b>4</b>	<b>Instrumentation and calibration .....</b>	<b>15</b>
<b>4.1</b>	<b>Instrumentation .....</b>	<b>15</b>
<b>4.2</b>	<b>Calibration .....</b>	<b>15</b>
<b>5</b>	<b>Test setup .....</b>	<b>15</b>
<b>5.1</b>	<b>General .....</b>	<b>15</b>
<b>5.2</b>	<b>Test setup type 1 .....</b>	<b>15</b>
<b>5.3</b>	<b>Test setup type 2 .....</b>	<b>16</b>
<b>5.4</b>	<b>Test setup type 3 .....</b>	<b>18</b>
<b>6</b>	<b>Test procedure .....</b>	<b>19</b>
<b>6.1</b>	<b>General .....</b>	<b>19</b>
<b>6.2</b>	<b>Generation of sound field .....</b>	<b>19</b>
<b>6.3</b>	<b>Sound pressure level in the source room .....</b>	<b>19</b>
<b>6.4</b>	<b>Measurement of average sound intensity level on the measurement surface .....</b>	<b>20</b>
<b>6.4.1</b>	<b>General .....</b>	<b>20</b>
<b>6.4.2</b>	<b>Measurement surface .....</b>	<b>20</b>
<b>6.4.3</b>	<b>Qualification of the measurement surface .....</b>	<b>20</b>
<b>6.4.4</b>	<b>Scanning procedure .....</b>	<b>21</b>
<b>6.4.5</b>	<b>Procedure using discrete positions .....</b>	<b>22</b>
<b>6.4.6</b>	<b>Scanning procedure for one measurement area .....</b>	<b>22</b>
<b>6.4.7</b>	<b>Scanning procedure for a partial measurement surface <math>S_{mc}</math> .....</b>	<b>22</b>
<b>6.5</b>	<b>Background noise .....</b>	<b>23</b>
<b>6.6</b>	<b>Frequency range of measurements .....</b>	<b>23</b>
<b>7</b>	<b>Presentation of results .....</b>	<b>23</b>
<b>8</b>	<b>Quality of the measurements .....</b>	<b>23</b>
<b>8.1</b>	<b>Deviations from the requirements .....</b>	<b>23</b>
<b>8.2</b>	<b>Measurement uncertainties .....</b>	<b>23</b>
<b>9</b>	<b>Test report .....</b>	<b>24</b>
<b>Annex A (normative) Method to qualify the sound field on the surface of the test specimen in the source room .....</b>		<b>25</b>
<b>Figure A.1 -- Possible setup to achieve a constant distance of 10 mm .....</b>		<b>25</b>
<b>Table A.1 -- Maximum acceptable deviation values <math>L_c</math> .....</b>		<b>26</b>
<b>Bibliography .....</b>		<b>27</b>