

ISO 10302-1:2024-02 (E)

Acoustics - Measurement of airborne noise emitted and structure-borne vibration induced by small air-moving devices - Part 1: Airborne noise measurement

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
3.1 General definitions.....	2
3.2 Acoustical definitions.....	2
3.3 Aerodynamic definitions.....	3
4 Limitations of measurement	4
5 Design and performance requirements for test plenum	5
5.1 General.....	5
5.2 Test plenum: main assembly.....	6
5.3 Mounting panel assembly.....	6
5.4 Adjustable exit port assembly.....	7
5.5 Insertion loss of test plenum.....	7
5.6 Instrumentation for static pressure measurement.....	7
6 Installation	8
6.1 Installation of test plenum in test room.....	8
6.2 Direction of airflow.....	8
6.3 Mounting of air-moving device.....	8
7 Operation of air-moving device	8
7.1 Input power.....	8
7.1.1 Alternating current (AC) air-moving devices.....	8
7.1.2 Direct current (DC) air-moving devices.....	8
7.2 Points of operation (AC and DC air-moving devices).....	9
7.2.1 Required points of operation.....	9
7.2.2 Method A (conventional method).....	9
7.2.3 Method B (alternative method).....	9
7.2.4 Procedure.....	10
8 Measurement procedures	10
8.1 General.....	10
8.2 Microphone positions for measurements in an essentially free field over a reflecting plane.....	11
8.2.1 General.....	11
8.2.2 Fixed points on a hemisphere.....	11
8.2.3 Coaxial circular paths in five or more parallel planes.....	11
8.3 Preparations for measurements.....	11
8.4 Operational test of air-moving device.....	12
9 Measurement uncertainty	12
10 Information to be recorded	13
11 Information to be reported	13

Annex A (normative) **Micro-fan *p-q* curve measurement method** 24

Annex B (informative) **Effects of air density** 26

Annex C (informative) **Data formats for presentation** 27

Annex D (informative) **Air-moving device acoustical noise specification** 32

Annex E (informative) **Guidance on the development of information on measurement uncertainty** 33