

ISO 17208-3:2025-09 (E)

Underwater acoustics - Quantities and procedures for description and measurement of underwater sound from ships - Part 3: Requirements for measurements in shallow water

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | General measurement requirements | 5 |
| 4.1 | General | 5 |
| 4.2 | Test ship parameters | 5 |
| 4.3 | Frequency range | 6 |
| 4.4 | CPA distance | 6 |
| 4.5 | Test site selection | 6 |
| 4.6 | Sea surface conditions | 7 |
| 4.7 | Acoustic measuring instrumentation | 7 |
| 4.7.1 | System sensitivity | 7 |
| 4.7.2 | Frequency range and sampling rate | 8 |
| 4.7.3 | Directivity | 8 |
| 4.7.4 | System self-noise | 8 |
| 4.7.5 | Dynamic range | 9 |
| 4.7.6 | Full system calibration | 9 |
| 4.7.7 | Field calibration checks | 9 |
| 4.7.8 | Data quality | 9 |
| 4.8 | Distance measurement | 10 |
| 4.9 | Hydrophone deployment | 10 |
| 4.9.1 | General | 10 |
| 4.9.2 | Vessel based deployments | 11 |
| 4.9.3 | Static deployments (bottom-tethered systems) | 11 |
| 4.9.4 | General criteria for deployments | 11 |
| 4.9.5 | Minimization of self-noise | 11 |
| 5 | Measurement configuration | 12 |
| 5.1 | Number of hydrophones | 12 |
| 5.2 | Hydrophone deployment configuration | 12 |
| 5.3 | Test course and ship operation | 12 |
| 5.4 | Number of runs | 15 |
| 5.5 | Background noise measurement | 15 |
| 6 | Data processing | 16 |
| 6.1 | General | 16 |
| 6.2 | Calculation of sound pressure levels | 16 |
| 6.3 | Background noise adjustments | 16 |
| 6.4 | Sensitivity adjustments | 17 |
| 7 | Source level calculation | 18 |
| 7.1 | Calculation of source level | 18 |

| | | |
|-------|--|----|
| 7.2 | Hydrophone and run combination post-processing | 20 |
| 7.2.1 | Introduction | 20 |
| 7.2.2 | Multiple hydrophones | 20 |
| 7.2.3 | Multiple runs | 21 |
| 7.3 | Calculation of radiated noise level | 21 |
| 8 | Measurement uncertainty | 21 |
| 8.1 | Overview | 21 |
| 8.2 | Uncertainty in measurement of source level | 22 |
| 8.2.1 | Combined uncertainty | 22 |
| 8.2.2 | Uncertainty in measurement of sound pressure levels | 22 |
| 8.2.3 | Uncertainty in the source level computation | 22 |
| 8.2.4 | Variability of the source | 23 |
| 9 | Reporting of results | 23 |
| 9.1 | Records required from vessel under test | 23 |
| 9.2 | Records required from fixed range or deploying vessel | 24 |
| 9.3 | Reporting results | 25 |
| | Annex A (informative) Examples of deployment methods | 27 |
| | Annex B (informative) Mitigation of platform and deployment related noise | 31 |
| | Annex C (informative) Calculation of sound pressure level in decidecade bands | 33 |
| | Annex D (informative) Propagation loss calculation (SSCI) | 39 |
| | Annex E (informative) Non-standard additional source level calculation methods | 44 |
| | Annex F (informative) Evaluation of uncertainties | 49 |
| | Annex G (informative) Notes on records and example additional records that may be required by the trial authority | 56 |
| | Bibliography | 58 |