ISO 10846-3:2002-06 (E)

Acoustics and vibration - Laboratory measurement of vibro-acoustic transfer properties of resilient elements - Part 3: Indirect method for determination of the dynamic stiffness of resilient supports for translatory motion

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 2

3 Terms and definitions 3

4 Principles 5

5 Requirements for apparatus 6
5.1 Normal translations 6
5.2 Transverse translations 10
5.3 Suppression of unwanted vibrations 11

6 Criteria for adequacy of the test arrangement 15
6.1 Frequency range 15
6.2 Determination of upper frequency limit f3 16
6.3 Flanking transmission 19
6.4 Unwanted input vibrations 20
6.5 Accelerometers 21
6.6 Force transducers 21
6.7 Summation of signals 21
6.8 Analysers 21

7 Test procedures 21
7.1 Installation of the test elements 21
7.2 Mounting and connection of accelerometers 22
7.3 Mounting and connections of the vibration exciter 22
7.4 Source signal 22
7.5 Measurements 22
7.6 Test for linearity 23

8 Evaluation of test results 24
8.1 Evaluation of dynamic transfer stiffness 24
8.2 One-third-octave-band values of the frequency averaged dynamic transfer stiffness 24
8.3 Presentation of one-third-octave-band results 25
8.4 Presentation of narrow-band data 25

9 Information to be recorded 26

10 Test report 26

Annex A (informative) Transfer stiffness related to rotatory vibration components 28

Annex B (informative) Effect of symmetry on the transfer stiffness matrix 36

Annex C (informative) Static load-deflection curve 37

Bibliography 38